LED recessed downlight

Article no. 12412023



Light. For Generations.





Tender

LED-recessed spot, chrome, round. In a compact design, for installation in tool-less rapid assembly systems. Lamp holder: Plug&Play, Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Current: 350 mA, Power: 5.4W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 420lm, Colour temperature: 3.000 K, Light colour : White, Beam angle: 40°, Adjustability: Not adjustable, With control gear: No.

Article data	
Article no.	12412023
GTIN	4250047797494
Short description	LED recessed downlight
Material	Aluminium
Colour	Chrome
Type of surface	Glossy
Shape	Round
Outer diameter	55 mm
Built-in diameter	49 mm
Installation depth	82 mm
Hight	2 mm
Weight	0.148 kg

All technical data as well as, weight and measurements are based on rated values and had been carefully prepared. We reserve the right to make technical changes which are are important in progressing. Product pictures are examples and can vary from the original. Subject to errors. Date 24.07.2023 Orders are placed under our general terms and conditions under https://www.brumberg.com/en/terms-and-conditions/general-terms-and-conditions-of-sale/

LED recessed downlight

Article no. 12412023

BRUMBERG

Light. For Generations.

Lighting technology	
Colour temperature	3.000 K
Light colour	White
Light output	Direct
Luminous flux	420 lm
System efficiency	78 lm/W
Colour rendering	CRI > 80
Reflector	High-gloss
Beam angle	40°
Light sharing	Symmetric

Operating technology of the luminaire	
System output	5.4 W
Voltage type	DC
Current	350 mA
Lamp	LED
Lamp holder	Plug&Play
Protection class	
Degree of protection	IP20
Control	Depending of the ar

Mounting technology	
Mounting method	Re issee nounting
Place of installation	Ceilin, mounted
Adjustability	No' "djustable
Further references	J cover with thermal insulation material
Material cover	Glass transparent

Packing data	
Gross weight	0.164 kg
Length of packaging	85 mm
Packaging width	80 mm
Packaging hight	60 mm
Disposal at end of life	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.