Recessed ceiling spot Article no. 40536073



Light. For Generations.





Tender

Recessed ceiling spot, white, Square. In a compact design, for installation in tool-less rapid assembly systems. Lamp holder: Plug&Play, Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Current: 700 mA, Power: 25W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 1.560lm, Colour temperature: 3000 K, Light colour : White, Beam angle: 100°, Adjustability: Not adjustable, With control gear: No.

| Article data | |
|--------------------|-----------------------|
| Article no. | 40536073 |
| GTIN | 4250047797791 |
| Short description | Recessed ceiling spot |
| Material | Aluminium |
| Colour | White |
| Type of surface | Matt |
| Shape | Square |
| Built-in width | 170 mm |
| Built-in length | 170 mm |
| Installation depth | 60 mm |
| Length | 190 mm |
| Width | 190 mm |
| Weight | 0.949 kg |

All technical data as well as, weight and measurements are based on rated values and had been carefully prepared. We reserve the right to make technical changes which are are important in progressing. Product pictures are examples and can vary from the original. Subject to errors. Date 26.09.2022 Orders are placed under our general terms and conditions under https://www.brumberg.com/en/terms-and-conditions/general-terms-and-conditions-of-sale/

Recessed ceiling spot Article no. 40536073

BRUMBERG

Light. For Generations.

| Lighting technology | |
|---------------------|-----------|
| Colour temperature | 3000 K |
| Light colour | White |
| Light output | Direct |
| Luminous flux | 1,560 lm |
| System efficiency | 62 lm/W |
| Colour rendering | CRI > 80 |
| Reflector | Without |
| Beam angle | 100° |
| Light sharing | Symmetric |

| Operating technology of the luminaire | |
|---------------------------------------|---------------------------|
| System output | 25 W |
| Voltage type | DC |
| DC nominal voltage max | 24 V |
| Current | 700 mA |
| Lamp | LED |
| Lamp holder | Plug&Play |
| Protection class | |
| Degree of protection | IP20 |
| Control | Dimmi, depering on driver |
| | |

| Mounting technology | |
|-----------------------|---|
| Mounting method | Receised mounting |
| Place of installation | Ceiling-mounted |
| Adjustability | Nr. adjustable |
| Further references | No cover with thermal insulation material |
| Material cover | Plastic, opal |

| Packing data | |
|-------------------------|---|
| Gross weight | 1.11 kg |
| Length of packaging | 220 mm |
| Packaging width | 195 mm |
| Packaging hight | 107 mm |
| Disposal at end of life | This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment. |

All technical data as well as, weight and measurements are based on rated values and had been carefully prepared. We reserve the right to make technical changes which are are important in progressing. Product pictures are examples and can vary from the original. Subject to errors. Date 26.09.2022 Orders are placed under our general terms and conditions under https://www.brumberg.com/en/terms-and-conditions/general-terms-and-conditions-of-sale/