

Recessed ceiling spot

Article no. 12001073























Recessed ceiling light, white. Designed in a compact design for tool-free quick installation for recessed ceiling mounting. Version: without socket, Mounting type: recessed mounting, Mounting location: ceiling mounting, Material: aluminum, Protection rating on room side: to DIN EN 60529: IP20, Protection class: (EN 61140) III, Power: 3 W, Colour temperature: 3,000 K, Beam angle: 40°, Without control gear, Type of dimming: Dependent on control gear.

Article data	
Article no.	12001073
GTIN	4250047768319
Short description	Recessed ceiling spot
Material	Aluminium
Colour	White
Type of surface	Matt
Outer diameter	40 mm
Built-in diameter	32 mm
Installation depth	18 mm
Hight	23 mm
Weight	0.072 kg
Conformance	CE, UKCA



Recessed ceiling spot

Article no. 12001073

Lighting technology	
Colour temperature	3.000 K
Light output	Direct
Beam angle	40°
Light sharing	Symmetric
Adjustable color temperature	No

Operating technology of the luminaire	
System output	3 W
AC nominal voltage max	3 V
Current	700 mA
Lamp	LED
Lamp holder	Plug&Play
Protection class	
Degree of protection	IP20
Control	Depending on driver
Energy efficiency class	nicht erforderlich

Mounting technology	
Mounting method	Recessed mounting
Place of installation	Ceiling-mounted
Further references	No cover with thermal insulation material
Material cover	Glass transparent

Packing data	
Gross weight	0.08 kg
Length of packaging	65 mm
Packaging width	50 mm
Packaging hight	65 mm
	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately.
Disposal at end of life	By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.