

**Floor recessed light**

Article no. 14018223

Light.  
For Generations.

Entwurf

**Tender**

Ground recessed luminaire, stainless steel, round. Recessed mounting, Floor-mounted. Mounting method: Recessed mounting, Place of installation: Floor-mounted, Material: Stainless steel / Aluminium / Glass, Degree of protection: according to DIN EN 60529 IP67, Protection class: (EN 61140) I, Voltage: 220V bis 230V, Power: 18W, Luminous flux: 1.290lm, Colour temperature: 3.000 K, Light colour : White, Beam angle: 24°, Adjustability: Not adjustable, With control gear: Yes, Control: on/off.

Article data	
Article no.	14018223
GTIN	4250047791379
Short description	Floor recessed light
Material	Stainless steel / Aluminium / Glass
Colour	Stainless steel
Shape	Round
Outer diameter	210 mm
Built-in diameter	179 mm
Installation depth	220 mm
Weight	2.794 kg

**Floor recessed light**

Article no. 14018223

Light.  
For Generations.

Lighting technology	
Colour temperature	3.000 K
Light colour	White
Luminous flux	1,290 lm
System efficiency	72 lm/W
Colour rendering	CRI > 80
Beam angle	24°
Light sharing	Symmetric

Operating technology of the luminaire	
System output	18 W
Voltage type	AC
AC nominal voltage max	220 V
Frequenz max.	50 Hz
Lamp	LED
Protection class	I
Degree of protection	IP67
Control	on/off

Mounting technology	
Mounting method	Recessed mounting
Place of installation	Floor mounted
Adjustability	Not adjustable
Max. load	100 kg
Over rollable	No
Material cover	Glass transparent
Suitable for through-wiring	No

Packing data	
Gross weight	3.104 kg
Length of packaging	230 mm
Packaging width	230 mm
Packaging height	240 mm
Disposal at end of life	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.

Accessories	
-------------	--