

LED recessed downlight  
Article no. 12411073

Light.  
For Generations.



Entwurf



#### Tender

LED-recessed spot, white, round. In a compact design, for installation in tool-less rapid assembly systems. Lamp holder: Plug&Play, Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Current: 350 mA, Power: 6.2W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 590lm, Colour temperature: 3.000 K, Light colour : White, Beam angle: 40°, Adjustability: Not adjustable, With control gear: No.

Article data	
Article no.	12411073
GTIN	4250047794066
Short description	LED recessed downlight
Material	Aluminium
Colour	White
Type of surface	Matt
Shape	Round
Outer diameter	100 mm
Built-in diameter	82 mm
Installation depth	65 mm
Weight	0.197 kg

LED recessed downlight  
Article no. 12411073

Light.  
For Generations.

Lighting technology	
Colour temperature	3000 K
Light colour	White
Light output	Direct
Luminous flux	590 lm
System efficiency	95 lm/W
Colour rendering	CRI > 80
Reflector	High-gloss
Beam angle	40°
Light sharing	Symmetric

Operating technology of the luminaire	
System output	6.2 W
Voltage type	DC
Current	350 mA
Lamp	LED
Lamp holder	Plug&Play
Protection class	III
Degree of protection	IP20
Control	Dimming dependent on driver

Mounting technology	
Mounting method	Recessed mounting
Place of installation	Ceiling-mounted
Adjustability	Not adjustable
Further references	No cover with thermal insulation material

Packing data	
Gross weight	0.255 kg
Length of packaging	110 mm
Packaging width	110 mm
Packaging height	80 mm
Disposal at end of life	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.

Accessories	
-------------	--