

LED recessed spot
Article no. 12092263

Light.
For Generations.



Tender
recessed spot, titan, square. In a compact design, for installation in tool-less rapid assembly systems. Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Voltage: 12V, Power: 3.7W, Luminous flux: 220lm, Colour temperature: 3200 K, Light colour : White, Beam angle: 50°, Adjustability: Pivoted, With control gear: No.

Article data	
Article no.	12092263
GTIN	4250047782650
Short description	LED recessed spot
Material	Aluminium
Colour	Titanium
Type of surface	Matt
Shape	Square
Built-in diameter	58 mm
Installation depth	28 mm
Length	72 mm
Width	72 mm
Hight	10 mm
Weight	N.N.

LED recessed spot
Article no. 12092263

Light.
For Generations.

Lighting technology	
Colour temperature	3200 K
Light colour	White
Light output	Direct
Luminous flux	220 lm
System efficiency	59 lm/W
Colour rendering	CRI > 80
Reflector	High-gloss
Beam angle	50°
Light sharing	Symmetric

Operating technology of the luminaire	
System output	3.7 W
Voltage type	DC
DC nominal voltage max	12 V
Lamp	LED
Protection class	III
Degree of protection	IP20
Control	on/off

Mounting technology	
Mounting method	Recessed mounting
Place of installation	Ceiling-mounted
Adjustability	Pivoted
Swivel angle	15°
stamp	MM
Further references	No cover with thermal insulation material
Material cover	Plastic, transparent

Packing data	
Gross weight	0.173 kg
Length of packaging	85 mm
Packaging width	43 mm
Packaging height	84 mm
Disposal at end of life	<p>This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately.</p> <p>By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.</p>