

Recessed ceiling spot
Article no. 01-75079



Tender	
Recessed ceiling light, gold, round. Designed in a compact design for tool-free quick installation for recessed ceiling mounting. Version: GX5.3, Mounting type: Recessed mounting, Mounting location: Ceiling mounting, Protection rating on room side: to DIN EN 60529: IP20, Protection class: (EN 61140) III, Voltage: 12V, Power: 50 W, Number of bulbs / sockets: 1 piece, without control gear, Type of dimming: Dependent on control gear.	

Article data	
Article no.	01-75079
GTIN	4250047732426
Short description	Recessed ceiling spot
Colour	Gold
Shape	Round
Outer diameter	110 mm
Weight	0.135 kg
Conformance	CE, UKCA

Recessed ceiling spot

Article no. 01-75079

Operating technology of the luminaire	
Voltage type	AC/DC
AC nominal voltage max	12 V
Frequency max	50 Hz
Lamp	For LED-retrofill lamp
Lamp holder	GX5.3
Protection class	III
Degree of protection	IP20
Control	Depending on driver
Energy efficiency class	nicht erforderlich

Mounting technology	
Mounting method	Recessed mounting
Place of installation	Ceiling-mounted
Further references	No cover with thermal insulation material

Packing data	
Gross weight	0.15 kg
Length of packaging	105 mm
Packaging width	105 mm
Packaging height	50 mm
Disposal at end of life	<p>This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately.</p> <p>By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.</p>

Compatible LED-modu-							
Article no.	Power	Beam angle	Colour temperature	Colour rendering	Luminous flux	Input	Hight LED-Modul
12925003	3 W	38°	2.700 K	CRI > 80	290 lm	350 mA	40 mm