

LED recessed downlight

Article no. 12052173

Licht.
Für Generationen.



Entwurf



Tender

LED recessed downlight, white, square. In a compact design, for installation in tool-less rapid assembly systems. Lamp holder: Plug&Play, Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium, Degree of protection: according to DIN EN 60529 IP65, Protection class: (EN 61140) III, Current: 350 mA, Power: 1.2W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 70lm, Colour temperature: 3.100 K, Light colour : White, Beam angle: 45°, Adjustability: Not adjustable, With control gear: No.

Article data	
Article no.	12052173
GTIN	4250047774457
Kurzbeschreibung	LED recessed downlight
Material	Aluminium
Colour	White
Type of surface	Matt
Shape	Square
Built-in diameter	23 mm
Installation depth	47 mm
Length	27 mm
Width	27 mm
weight	0.045 kg

LED recessed downlight

Article no. 12052173

Licht.
Für Generationen.

Lighting technology	
Colour temperature	3100 K
Light colour	White
Light output	Direct
Luminous flux	70 lm
System efficiency	58 lm/W
Colour rendering	CRI > 80
Reflector	Without
Beam angle	45 °
Light sharing	Symmetric

Operating technology of the luminaires	
System output	1.2 W
Voltage type	DC
Current	350 mA
Lamp	LED
Lamp holder	Plug&Play
Protection class	III
Degree of protection	IP65

Mounting technology	
Mounting method	Recessed mounting
Place of installation	Ceiling-mounted
Adjustability	Not adjustable
Further references	No cover with thermal insulation material
Material cover	Glass transparent

Packing data	
Gross weight	0.06 kg
Length of packaging	70 mm
Packaging width	47 mm
Packaging height	81 mm