

RESEDA LED power supply 12 V DC to 3900.. / 3901.., on/off switchable

Article no. 3559

Light.
For Generations.**Tender**

LED power supply 12 V DC to 3900.. / 3901.. on/off switchable, Round. Ceiling cut-out Installation depth mm, Outer diameter 57,5 mm, Weight 0,059 kg, ,with max: 10 W , Delivery without bulb.Housing material: Plastic, Permissible ambient temperature (ta): -20 °C - +25 °C, Protection class (EN 61140): II, Degree of protection (DIN EN 60529): IP20, .For connection to an external driver, which is not included in the scope of delivery of the luminaire. on/off switchable.

| Article data | |
|-------------------|--|
| Article no. | 3559 |
| GTIN | 4250047751137 |
| Series name | RESEDA |
| Short description | LED power supply 12 V DC to 3900.. / 3901.., on/off switchable |
| Material | Plastic |
| Shape | Round |
| Outer diameter | 57.5 mm |
| Hight | 19 mm |
| Weight | 0.059 kg |

RESEDA LED power supply 12 V DC to 3900.. / 3901.., on/off switchable

Article no. 3559

Light.
For Generations.

| Operating technology of driver | |
|--------------------------------|----------------|
| AC nominal voltage max | 230 V |
| Frequenz max. | 50 Hz |
| Protection class | II |
| Degree of protection | IP20 |
| Power min | 0.1 W |
| Power | 10 W |
| Control | on/off |
| Environment temperature (ta) | 0°C up to 40°C |
| Measure point (tc) | max. +70 °C |

| Packing data | |
|-------------------------|---|
| Gross weight | 0.074 kg |
| Length of packaging | 85 mm |
| Packaging width | 42 mm |
| Packaging height | 84 mm |
| Disposal at end of life | This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment. |