

Recessed ceiling spot

Article no. 12272153











Tende

Recessed ceiling spot, Square. Ceiling cut-out Installation depth mm, Length 110 mm, Width 110 mm, Weight 0,459 kg, with rotattions-symmetrical, deep, wide distributed light intensity.. Power 14 W, Light colour warm white, Correlated color temprature (CCT) 2.700 K, Colour rendering index , , Colour: Nickel, Permissible ambient temperature (ta): -20 °C - +25 °C, Protection class (EN 61140): III, Degree of protection (DIN EN 60529): IP20. For connection to an external driver, which is not included in the scope of delivery of the luminaire. Depending on driver dimmable.

Article data	
Article no.	12272153
GTIN	4250047794806
Short description	Recessed ceiling spot
Colour	Nickel
Type of surface	Matt
Shape	Square
Length	110 mm
Width	110 mm
Weight	0.459 kg
Conformance	CE, UKCA

Lighting technology	
Colour temperature	2.700 K
System efficiency	14 lm/W
Reflector	High-gloss
Light sharing	Symmetric
Adjustable color temperature	No



Recessed ceiling spot

Article no. 12272153

Operating technology of the luminaire	
Current	700 mA
Lamp	LED
Lamp holder	Without fitting
Protection class	
Degree of protection	IP20
Control	Depending on driver
Energy efficiency class	nicht erforderlich

Mounting technology	
Mounting method	Recessed mounting
Place of installation	Ceiling-mounted

Packing data	
Gross weight	0.51 kg
Length of packaging	170 mm
Packaging width	210 mm
Packaging hight	180 mm
Disposal at end of life	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.