

Recessed ceiling spot
Article no. 02300006

Light.
For Generations.



Tender	
Recessed ceiling spot, , Round.In a compact design, for installation in tool-less rapid assembly systems.Lamp holder: GX5.3, Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Voltage: 12V, Power: 35 W, Amount of light sources / fittings: 1 Qty, Adjustability: Not adjustable, without control gear, Control: Other.	

Article data	
Article no.	02300006
GTIN	4251433901181
Short description	Recessed ceiling spot
Material	Aluminium
Colour	Black / Alu
Type of surface	Glossy
Shape	Angular
Outer diameter	89 mm
Built-in diameter	68 mm
Installation depth	60 mm
Length	89 mm
Width	89 mm
Hight	10 mm
Weight	0.179 kg
Conformance	CE

Recessed ceiling spot
Article no. 02300006

Light.
For Generations.

Operating technology of the luminaire	
System output	35 W
Voltage type	AC/DC
AC nominal voltage max	12 V
Frequency max	50 Hz
Lamp	For LED-retrofill lamp
Lamp holder	GX5.3
Protection class	III
Degree of protection	IP20
Control	Depending on driver

Mounting technology	
Mounting method	Recessed mounting
Place of installation	Ceiling-mounted
Adjustability	Not adjustable
Further references	No cover with thermal insulation material
Material cover	Glass structured

Packing data	
Gross weight	0.199 kg
Length of packaging	110 mm
Packaging width	110 mm
Packaging hight	40 mm
Disposal at end of life	<p>This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately.</p> <p>By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.</p>

Compatible LED-modules						
Article no.	Power	Beam angle	Colour tempera- ture	Luminous flux	Input	Hight LED-Modul
12925003	3 W	38°	2.700 K	290 lm	350 mA	40 mm