

Recessed ceiling spot

Article no. 1938.15





Tendei

Recessed ceiling light, nickel, round. Designed in a compact design for tool-free quick installation for recessed ceiling mounting. Version: GX5.3, Mounting type: Recessed mounting, Mounting location: Ceiling mounting, Material: Steel, Protection rating on room side: to DIN EN 60529: IP20, Protection class: (EN 61140) III, Voltage: 12V, Power: 50 W, Number of bulbs / sockets: 1, Adjustment: Swivel, without control gear, Type of dimming: Dependent on control gear.

Article data					
Article no.	1938.15				
GTIN	4250047762294				
Short description	Recessed ceiling spot				
Material	Steel				
Colour	Nickel				
Type of surface	Matt				
Shape	Round				
Outer diameter	80 mm				
Built-in diameter	68 mm				
Installation depth	60 mm				
Weight	0.130 kg				
Conformance	CE, UKCA				



Recessed ceiling spot

Article no. 1938.15

Operating technology of the luminaire	
System output	50 W
Voltage type	AC/DC
AC nominal voltage max	12 V
Frequency max	50 Hz
Lamp	For LED-retrofill lamp
Lamp holder	GX5.3
Protection class	
Degree of protection	IP20
Control	Depending on driver
Energy efficiency class	nicht erforderlich

Mounting technology	
Mounting method	Recessed mounting
Place of installation	Ceiling-mounted
Adjustability	Pivoted
Swivel angle	25°
Further references	No cover with thermal insulation material
Circlip	Without circlip

Packing data	
Gross weight	0.147 kg
Length of packaging	85 mm
Packaging width	43 mm
Packaging hight	84 mm
Disposal at end of life	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. By disposing of electrical waste and other old or defective electronics separately, you
	support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.

Compatible LED-modu-							
Article no.	Power	Beam angle	Colour tempera- ture	Colour rende- ring	Luminous flux	Input	Hight LED-Modul
12925003	3 W	38°	2.700 K	CRI > 80	290 lm	350 mA	40 mm