MAXI LED track spotlight

Article no. 88398173





Tender

Round LED track spotlight, rotatable and tiltable, DALI dimmable, height 263 mm, weight 1.269 kg, with rotationally symmetrical narrowwide beam light distribution. Rated power 1 x 32 W, light color warm white, most similar color temperature (CCT) 3,000 K, general color rendering index CRI > 90, housing material: aluminum / glass / plastic, color: textured white, permissible ambient temperature (ta): -20 °C - +25 °C, protection class (EN 61140): I, degree of protection (DIN EN 60529): IP20. With electronic control gear, DALI dimmable.

| Article data | |
|-------------------|-----------------------------|
| Article no. | 88398173 |
| GTIN | 4251433954255 |
| Series name | MAXI |
| Short description | LED track spotlight |
| Material | Aluminium / Glass / Plastic |
| Colour | White |
| Type of surface | Structure |
| Shape | Round |
| Length | 235 mm |
| Hight | 263 mm |
| Weight | 1.269 kg |
| Conformance | CE, UKCA |

All technical data as well as, weight and measurements are based on rated values and had been carefully prepared. We reserve the right to make technical changes which are are important in progressing. Product pictures are examples and can vary from the original. Subject to errors. Date 08.04.2025 Orders are placed under our general terms and conditions under https://www.brumberg.com/en/terms-and-conditions/general-terms-and-conditions-of-sale/



MAXI LED track spotlight

Article no. 88398173

| Lighting technology | |
|------------------------------|------------|
| Colour temperature | 3.000 K |
| Light colour | White |
| System efficiency | 32 lm/W |
| Colour rendering | CRI > 90 |
| Reflector | High-gloss |
| Light sharing | Symmetric |
| Adjustable color temperature | No |

| Operating technology of the luminaire | |
|---------------------------------------|--|
| System output | 32 W |
| Voltage type | AC |
| AC nominal voltage max | 230 V |
| Frequency max | 50 Hz |
| Lamp | LED |
| Lamp holder | Without fitting |
| Protection class | |
| Degree of protection | IP20 |
| Control | DALI |
| Rulh abanga pagaible | The light source of this luminaire may only be replaced by the manufacturer or a service |
| Bulb change possible | technician commissioned by him or a similarly qualified person. |
| Energy efficiency class | nicht erforderlich |

| Mounting technology | |
|-----------------------------|-------------------------------|
| Mounting method | Conductor rail mounting |
| Place of installation | Ceiling-mounted |
| Adjustability | Rotatable and adjustable head |
| Swivel angle | 180° |
| Rotation angle | 355° |
| Head adjustable angle | 180° |
| Suitable for through-wiring | No |

| Packing data | |
|-------------------------|--|
| Gross weight | 1.395 kg |
| Length of packaging | 300 mm |
| Packaging width | 200 mm |
| Packaging hight | 150 mm |
| | This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. |
| Disposal at end of life | By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment. |

MAXI LED track spotlight

Article no. 88398173

| Optional accessories |
|---|
| Article no.: 81397182 |
| Honeycomb grid for spot MAXI |
| |
| https://www.brumberg.com/fileadmin/products/Datenblatt_81397182_2021_DE.pdf |
| Article no.: 81397171 |
| Schade for spot MAXI |
| |
| https://www.brumberg.com/fileadmin/products/Datenblatt_81397171_2021_DE.pdf |
| Article no.: 81397181 |
| Schade for spot MAXI |
| |
| https://www.brumberg.com/fileadmin/products/Datenblatt_81397181_2021_DE.pdf |
| Article no.: 81397180 |
| Glare protection for spot MAXI |
| |
| https://www.brumberg.com/fileadmin/products/Datenblatt_81397180_2021_DE.pdf |
| Article no.: 81397170 |
| Glare protection for spot MAXI |
| |
| https://www.brumberg.com/fileadmin/products/Detenblatt_01207170_2021_DE.pdf |
| https://www.brumberg.com/fileadmin/products/Datenblatt_81397170_2021_DE.pdf |