


LED power supply unit 24 V DC, DALI-2 dimmable

Article no. 17250000







Tondor

LED power supply unit 24 V DC, DALI-2 dimmable, white, rectangular. Material: Plastic, Protection rating on room side: to DIN EN 60529: IP20, Protection class: (EN 61140) II, Voltage: 230V AC, Power: 45 W, Dimmable: Yes, Type of dimming: DALI-2.

Product Benefits

- Plastic housing incl. strain relief
- protection class II
- dimmable via DALI-2
- Measuring point Tc (max) 85°C

Article data	
Article no.	17250000
GTIN	4251433957577
Short description	LED power supply unit 24 V DC, DALI-2 dimmable
Material	Plastic
Colour	White
Shape	Rectangular
Length	187 mm
Width	45 mm
Hight	31 mm
Weight	0.224 kg
stamp	ENEC, EL
Conformance	CE, UKCA



LED power supply unit 24 V DC, DALI-2 dimmable

Article no. 17250000

Operating technology of driver	
AC nominal voltage min	176 V
AC nominal voltage max	264 V
Frequency min	50 Hz
Frequency max	60 Hz
DC nominal voltage min	176 V
DC nominal voltage max	280 V
Protection class	
Degree of protection	IP20
Power min	1 W
Power max.	45 W
Starting current	40 A, 250 μs
Suitable for emergency lighting	No
measure point (tc)	85 °C
Power factor	0.95
max. no. lights on B10 A	13
max. no. lights on B16 A	19
max. no. lights on C16 A	24
max. no. lights on C10 A	16
Output voltage max	24.00 V
Output voltage min.	24.00 V
Control	DALI-2, PUSH-Dimm
Connection type-primary	Screw-in connection
Connection type-secondary	Screwed terminal
Number of poles	5
Flicker-free	Yes
Average nominal lifespan	44000 h

Packing data	
Gross weight	0.258 kg
Length of packaging	220 mm
Packaging width	50 mm
Packaging hight	37 mm
Disposal at end of life	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.