


## LED driver 24V DC, switchable

Article no. 17227000







## Tende

LED power supply unit 24 V DC, switchable, white, rectangular. This power supply unit is protected by fuses against overvoltage and short circuits as well as thermal and electrical overload. Material: aluminum, Protection class on room side: according to DIN EN 60529: IP65, Protection class: (EN 61140) I, Voltage: 24 V DC, Power: 320 W, Dimmable: No, Type of dimming: Switchable.

| Article data                  |                               |
|-------------------------------|-------------------------------|
| Article no.                   | 17227000                      |
| GTIN                          | 4251433954750                 |
| Short description             | LED driver 24V DC, switchable |
| Material                      | Aluminium                     |
| Colour                        | White                         |
| Shape                         | Rectangular                   |
| Length                        | 252 mm                        |
| Width                         | 90 mm                         |
| Hight                         | 44 mm                         |
| Weight                        | 1.828 kg                      |
| Length of the connection line | 300 mm                        |
| stamp                         | MM                            |
| Conformance                   | CE                            |



## LED driver 24V DC, switchable

Article no. 17227000

| Operating technology of driver  |                 |
|---------------------------------|-----------------|
| AC nominal voltage min          | 90 V            |
| AC nominal voltage max          | 305 V           |
| Frequency min                   | 47 Hz           |
| Frequency max                   | 63 Hz           |
| DC nominal voltage min          | 127 V           |
| DC nominal voltage max          | 431 V           |
| Protection class                |                 |
| Degree of protection            | IP65            |
| Power min                       | 1 W             |
| Power                           | 320 W           |
| Output_ripple_current           | 150             |
| Starting current                | 70 A, 1.010 μs  |
| Suitable for emergency lighting | No              |
| measure point (tc)              | 90 °C           |
| Power factor                    | 0.95            |
| max. no. lights on B16 A        | 1               |
| max. no. lights on C16 A        | 2               |
| Output voltage max              | 26.00 V         |
| Output voltage min.             | 21.00 V         |
| Control                         | on/off          |
| Connection type-primary         | Cable           |
| Connection type-secondary       | Open ends       |
| Number of poles                 | 3               |
| Enviroment temprature (ta)      | 0 °C bis +40 °C |
| Measure point (tc)              | max. +90 °C     |
| Average nominal lifespan        | 100000 h        |
| Output current                  | 13,34 A mA      |
| Length of the connection line   | 300 mm          |

| Mounting technology         |  |
|-----------------------------|--|
| Further references          | Outdoor No cover with thermal insulation material Control gear suitable for installation in fal- |
|                             | se ceiling   |
| Application                 | Indoor/Outdoor   |
| Suitable for through-wiring | No   |

| Packing data            |  |
|-------------------------|--|
| Gross weight            | 1.938 kg   |
| Length of packaging     | 335 mm   |
| Packaging width         | 125 mm   |
| Packaging hight         | 56 mm  |
|                         | This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately.  |
| Disposal at end of life | By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment. |