



UGLOS LED wall recessed light
Article no. 10166223



Tender	
Rectangular LED recessed wall light, ceiling cut-out L x W 79 x 88 mm installation depth 70 mm, length 90 mm, width 100 mm, weight 0.476 kg, with rotationally symmetrical deep-wide light distribution. Cover glass transparent, rated luminous flux 40 lm, rated wattage 1 x 1 W, light color warm white, most similar color temperature (CCT) 3,000 K, general color rendering index CRI > 80, housing material: stainless steel / steel / glass, color: stainless steel, permissible ambient temperature (ta): -20 °C - +25 °C, protection class (EN 61140): III, degree of protection (DIN EN 60529): IP20. For connection to an external control gear, which is not included with the luminaire. other dimmable.	

Article data	
Article no.	10166223
GTIN	4251433907299
Series name	UGLOS
Short description	LED wall recessed light
Material	Stainless steel / Steel / Glass
Colour	Stainless steel
Type of surface	Matt
Shape	Rectangular
Length	90 mm
Width	100 mm
Built-in length	79 mm
Built-in width	88 mm
Installation depth	70 mm
Hight	90 mm
Weight	0.476 kg
Conformance	CE, UKCA

UGLOS LED wall recessed light

Article no. 10166223

Lighting technology	
Colour temperature	3.000 K
Light colour	White
Luminous flux	40 lm
System efficiency	40 lm/W
Colour rendering	CRI > 80
Reflector	Matt
Light sharing	Symmetric
Adjustable color temperature	No

Operating technology of the luminaire	
System output	1 W
Voltage type	DC
Current	350 mA
Lamp	LED
Lamp holder	Plug&Play
Protection class	III
Degree of protection	IP20
Dimmable	Depending on type of control gear
Control	Other
Bulb change possible	The light source of this luminaire may only be replaced by the manufacturer or a service technician commissioned by him or a similarly qualified person.
Energy efficiency class	nicht erforderlich

Mounting technology	
Mounting method	Recessed mounting
Place of installation	Wall-mounted
Adjustability	Not adjustable
Material cover	Glass transparent

Packing data	
Gross weight	0.52 kg
Length of packaging	105 mm
Packaging width	95 mm
Packaging height	85 mm
Disposal at end of life	<p>This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately.</p> <p>By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.</p>

Required accessories	
Article no.: 17665000 LED converter 350 mA, switchable Power: 1 - 3,2 W, Plug&Play Dimensions: 52 mm x 30 mm x 23 mm https://www.brumberg.com/fileadmin/products/Datenblatt_17665000_2021_DE.pdf	