


**QUALITYFLEX Select LED flex lighting, 5 m, CRI > 90, 9,6 W / m,****IP00**

Article no. 15202024

Light.  
For Generations.**Tender**

LED flex lighting, 5 m, CRI > 90, 9,6 W / m, IP00, white, 2.400K, CRI > 90. LED flex lighting Length: 5000.0 mm Lamp power per meter: 9.6 W/m, Luminous flux per meter: 760.0 lm/m, Degree of protection: IP00, Protection class: III, Voltage: 24V DC, Beam angle: 120.0 °, 120 LEDs per meter, Chip distance (Short Pitch) : 8,3mm. For individual application, the LED flex board can be used all 50 mm be cut back. The maximum system length of 5.000mm must not be exceeded with one feed-in.

**Product Benefits**

- Suitable for indoor applications (IP00).
- Decorative lighting of furniture, objects and light coves.
- Indirect lighting in living areas.
- Length 5000 mm with a pitch of 50 mm.
- Available in 2400 K, 2700 K, 3000 K, 4000 K and 6000 K.
- Dimmable with appropriate accessories.

**QUALITYFLEX Select LED flex lighting, 5 m, CRI > 90, 9,6 W / m, IP00**

Article no. 15202024

Light.  
For Generations.

Article data	
Article no.	15202024
GTIN	4251433913238
Series name	QUALITYFLEX Select
Short description	LED flex lighting, 5 m, CRI > 90, 9,6 W / m, IP00
Colour	White
Length	5,000 mm
Width	8 mm
Height	1.4 mm
Scope of delivery	incl. 1 x mounting instructions, 5 x identification labels
Weight	0.091 kg
Length of the connection line	350 mm
stamp	UKCA

Lighting technology	
Colour temperature	2.400 K
Light colour	White
Color Temperature 1	2,400 K
Luminous flux per meter	760 lm/m
System efficiency	79 lm/W
McAdam-Step	McAdam-Step 5
Colour rendering	CRI > 90
Beam angle	120°
Adjustable color temperature	No

Operating technology of the luminaire	
Lamp power per meter	9.6 W/m
Voltage type	DC
DC nominal voltage max	24 V
Lamp	LED
Protection class	III
Degree of protection	IP00
Ambient temperature	-10 °C up to +40 °C
Dimmable	Yes
Wire number	2
Control	Depending on driver
Length of the connection line	350 mm
Kabelbelegung	red = + pole black = - pole
Design of the connecting cable	both sides
Bulb change possible	No
Energy efficiency class	F

Operating technology of QualityFlex	
Short Pitch	8.3 mm
Number of lamps per meter	120 Qty
Length of individual sections	50 mm
Smallest bend radius	25 mm
Length	5,000 mm
Maximum module length	5,000 mm
Circuit type	Parallel conduction
LED Type	2835 LED

**QUALITYFLEX Select LED flex lighting, 5 m, CRI > 90, 9,6 W / m, IP00**

Article no. 15202024

Light.  
For Generations.

Packing data	
Gross weight	0.137 kg
Length of packaging	220 mm
Packaging width	240 mm
Packaging height	20 mm
Disposal at end of life	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.

Compatible Driver						
Article no.	Power min	Power	Control	Length	Width	Height
17206000	1 W	20 W	1-10 V	146 mm	55 mm	19 mm
17207000	1 W	30 W	on/off	160 mm	50 mm	22 mm
17214000	1 W	7.2 W	on/off	68 mm	35 mm	21 mm
17223000	1 W	75 W	on/off	185 mm	60 mm	31 mm
17224000	1 W	100 W	on/off	199 mm	63 mm	36 mm
17225000	1 W	150 W	on/off	219 mm	63 mm	36 mm
17226000	1 W	240 W	on/off	244 mm	71 mm	38 mm
17230000			Trailing-edge phase			
17240000			on/off			

Compatible Controller						
Article no.	Power min	Power	Control	Length	Width	Height
17502000	0 W	120 W	DALI	183 mm	33 mm	23 mm
18151000	1 W	240 W	KNX	170 mm	59 mm	30 mm
18152000	1 W	240 W	DALI-DT6	170 mm	59 mm	30 mm
18153000	1 W	240 W	DMX	170 mm	59 mm	30 mm
18154000	1 W	240 W	1-10 V	170 mm	59 mm	30 mm
18161000	1 W	240 W	KNX	72 mm	90 mm	70 mm
18162000	1 W	240 W	DALI-DT6	54 mm	110 mm	66 mm
18164000	1 W	240 W	1-10 V	54 mm	110 mm	66 mm
17528000	1 W	240 W	Wireless technology control			
17511000	1 W	240 W	Wireless technology control	145 mm	46.5 mm	16 mm
18157000	48 W	240 W	ZigBee	145 mm	46.5 mm	16 mm
18192000	120 W	240 W	Wireless technology control	160 mm	45 mm	18 mm

**QUALITYFLEX Select LED flex lighting, 5 m, CRI > 90, 9,6 W / m, IP00**

Article no. 15202024

Light.  
For Generations.

Compatible Profiles				
Short description	Series name	Length	Width	Height
Surface-mounted profile 53600070	P01-10	2,000 mm	20 mm	8 mm
Surface-mounted profile 53605260	P02-10	2,000 mm	17.5 mm	25 mm
Surface-mounted profile 53601080	P03-12	2,000 mm	17.8 mm	10.8 mm
Surface-mounted profile 53602070	P04-14	2,000 mm	24 mm	9 mm
Surface-mounted profile 53604080	P05-14	2,000 mm	17.5 mm	8.6 mm
Surface-mounted profile 53603070	P06-20	2,000 mm	23 mm	25.1 mm
LED surface-mounted profile 53606070	P30-30	2,000 mm	33.4 mm	29.6 mm
Surface-mounted profile 53607080	P16-16	2,000 mm	18.8 mm	18.6 mm
Surface-mounted profile, flat 53380261	ONE		17.6 mm	6 mm
Surface-mounted profile, high 53381302	ONE		17.6 mm	15.9 mm
Recessed profile 53651070	P31-10	2,000 mm	24 mm	7 mm
Recessed profile 53653070	P34-14	2,000 mm	28 mm	8 mm
Recessed profile 53657080	P35-14	2,000 mm	24.5 mm	9 mm
Recessed profile 53654070	P36-20	2,000 mm	30 mm	20.4 mm
LED recessed profile 53759070	P40-30	2,000 mm	44.4 mm	24 mm
Plaster profile 53655070	P37-30	2,000 mm	63.4 mm	15.9 mm
Plaster profile 53656070	P38-30	2,000 mm	63.4 mm	24 mm
Wall recessed profile 53650260	P32-12	2,000 mm	19.1 mm	81 mm
Floor recessed profile 53652260	P33-12	2,000 mm	15.8 mm	13.7 mm
Surface-mounted corner profile 53700070	P60-10	2,000 mm	20 mm	16 mm
Surface-mounted corner profile 53701260	P61-10	2,000 mm	14.5 mm	14.5 mm
Surface-mounted corner profile 53702070	P62-14	2,000 mm	24 mm	19.4 mm
Surface-mounted corner profile 53703260	P63-14	2,000 mm	17.5 mm	17.5 mm
Surface-mounted corner profile 53385261	ONE		24 mm	19.4 mm
Flexible profile 53753070	P72-12	2,000 mm	20 mm	3.3 mm
Wall surface-mounted profile 53754070	P73-12	2,000 mm	17.8 mm	46.1 mm
Wall surface-mounted profile 53751260	P74-14	2,000 mm	18.5 mm	55 mm
Ceiling recessed profile with wall mounting 53755260	P75-14	2,000 mm	28 mm	28 mm
Flat profile P76-16 53756070	P76-16	2,000 mm	20.5 mm	3.8 mm
Surface-mounted cooling profile 53760260	P02-10		20 mm	17 mm
Surface-mounted cooling profile 53382261	ONE		20.5 mm	3.8 mm

All measurements are based on rated values and had been carefully prepared. We reserve the right to make technical changes which are in progress. Product pictures are examples and can vary from the original. Subject to errors.

Date: 13.05.2024 Orders are placed under our general terms and conditions under <https://www.brumberg.com/en/terms-and-conditions/general-terms-and-conditions-of-sale/>

**QUALITYFLEX Select LED flex lighting, 5 m, CRI > 90, 9,6 W / m,  
IP00**

Article no. 15202024

Light.  
For Generations.