


## MIRROR LED wall surface mounted mirror luminaire, IP44

Article no. 58302003















Square surface-mounted LED wall-mounted mirror light, IP44, switchable, , luminaire width 800 mm, height 800 mm, weight 12.000 kg, with rotationally symmetrical narrow-wide beam light distribution. Rated luminous flux 4,124 lm, rated wattage 2 x 20 W, light color warm white, most similar color temperature (CCT) 3,000 K, general color rendering index CRI > 90, service life L70/B50 at 25 °C: 60,000 h, housing material: crystal mirror glass / aluminum, permissible ambient temperature (ta): -20 °C - +25 °C, protection class (EN 61140): II, degree of protection (DIN EN 60529): IP44. With electronic control gear, switchable.

| Article data      |   |
|-------------------|---|
| Article no.       | 58302003  |
| GTIN              | 4251433921387                                   |
| Series name       | MIRROR  |
| Short description | LED wall surface mounted mirror luminaire, IP44 |
| Material          | Crystal plate glass / Aluminium                 |
| Shape             | Square  |
| Width             | 800 mm  |
| Hight             | 800 mm  |
| Weight            | 12.000 kg                                       |
| Conformance       | CE, UKCA  |



## MIRROR LED wall surface mounted mirror luminaire, IP44

Article no. 58302003

| Lighting technology          |           |
|------------------------------|-----------|
| Colour temperature           | 3.000 K   |
| Light colour                 | White     |
| Luminous flux                | 4,124 lm  |
| System efficiency            | 206 lm/W  |
| Colour rendering             | CRI > 90  |
| Reflector                    | Without   |
| Light sharing                | Symmetric |
| Adjustable color temperature | No        |

| Operating technology of the luminaire |  |
|---------------------------------------|--|
| System output                         | 40 W   |
| Voltage type                          | AC   |
| AC nominal voltage max                | 230 V  |
| Frequency max                         | 50 Hz  |
| Lamp                                  | LED  |
| Lamp holder                           | Without fitting  |
| Protection class                      |  |
| Degree of protection                  | IP44   |
| Dimmable                              | No   |
| Control                               | on/off   |
| Bulb change possible                  | The light source of this luminaire may only be replaced by the manufacturer or a service |
| Dulb change possible                  | technician commissioned by him or a similarly qualified person.                          |
| Rated life time L70/B50 at 25 °C      | 60,000 h   |

| Mounting technology   |                  |
|-----------------------|------------------|
| Mounting method       | Surface mounting |
| Place of installation | Wall-mounted     |
| Adjustability         | Not adjustable   |

| Packing data            |   |
|-------------------------|---|
| Gross weight            | 12.5 kg   |
| Length of packaging     | 830 mm  |
| Packaging width         | 830 mm  |
| Packaging hight         | 60 mm   |
|                         | This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. |
| Disposal at end of life | By disposing of electrical waste and other old or defective electronics separately, you                                     |
|                         | support recycling or other forms of re-use. In that way you help to take care and to avoid that                             |
|                         | harmful substances get into the environment.  |