

LED-Dimmer 12-24 V DC, Casambi dimmbar

Article no. 18170000

Light.
For Generations.**Tender**

LED-Dimmer 12-24 V DC, Casambi dimmbar. Steuerung per Casambi App.Per Smartphone und Bluetooth direkt auf die LEDs zugreifen.<P/>Der Casambi 4-Kanal-PWM-Dimmer kann bis zu vier Kanäle steuern und ist deshalb ideal für Qualityflex ONE + COB sowie auch RGBW- und TunableWhite-Anwendungen.<P/>Mehrere Geräte bilden automatisch ein Mesh-Netzwerk, das von jedem beliebigen Punkt aus gesteuert werden kann. Diese Netzwerke kommunizieren drahtlos direkt mit dem Smartphone oder Tablet. Dadurch ist kein externes Gateway oder Wireless LAN-Netzwerk erforderlich.<P/>Das Gerät ist für verschiedene Betriebsmodi einstellbar.<P/>getrennte Kanäle Ausgang 1-4, max. 6ATunableWhite Ausgang 1+2, max. 6ARGBW
Ausgang 1-4, max. 6A <P/>Zum Betrieb wird eine externe Spannungsversorgung (24V DC) benötigt. <P/></TEXT> Material: Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Voltage: 12V 24V, Power: 144W.

Article data	
Article no.	18170000
GTIN	4251433955160
Short description	LED-Dimmer 12-24 V DC, Casambi dimmbar
Material	Plastic
Length	73 mm
Width	30 mm
Hight	18 mm
Weight	0.035 kg

LED-Dimmer 12-24 V DC, Casambi dimmbar

Article no. 18170000

Light.
For Generations.

Operating technology of driver	
Protection class	III
Degree of protection	IP20
Power min	0 W
Power	144 W
Control	Casambi
Environment temperature (ta)	-20 °C bis +45 °C
Measure point (tc)	max. +75 °C

Packing data	
Gross weight	0.095 kg
Length of packaging	70 mm
Packaging width	47 mm
Packaging height	81 mm
Disposal at end of life	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.

Compatible Driver						
Article no.	Power min	Power	Control	Length	Width	Hight
17240000		20 W	on/off	150 mm	40 mm	30 mm
17241000		40 W	on/off	210 mm	40 mm	30 mm
17242000		60 W	on/off	250 mm	40 mm	30 mm
17243000		120 W	on/off	300 mm	40 mm	30 mm
17244000		150 W	on/off	310 mm	40 mm	30 mm
17224000	1 W	100 W	on/off	199 mm	63 mm	36 mm
17225000	1 W	150 W	on/off	219 mm	63 mm	36 mm
17226000	1 W	240 W	on/off	244 mm	71 mm	38 mm
17214000	1 W	7.2 W	on/off	68 mm	35 mm	21 mm
17206000	1 W	20 W	1-10 V	146 mm	55 mm	19 mm
17207000	1 W	30 W	on/off	160 mm	50 mm	22 mm
17223000	1 W	75 W	on/off	185 mm	60 mm	31 mm
3506	0 W	20 W	1-10 V	146 mm	55 mm	19 mm
17221000	240 W	480 W	on/off	227 mm	125.5 mm	100 mm
17122000	1 W	120 W	on/off	219 mm	63 mm	36 mm
17672000	3.5 W	18 W	Casambi	146 mm	44 mm	30 mm