
BRUMBERG

LED power supply 24V DC, on/off switchable Article no. 17226000

Light. For Generations.







Tender

LED power supply 24V DC, on/off switchable, white, Rectangular. This power supply unit is equipped with safety devices which protect it against overvoltage, short-circuit as well as thermal and electric overloads. Material: Aluminium, Degree of protection: according to DIN EN 60529 IP65, Protection class: (EN 61140) I, Voltage: 24 V DC, Power: 240 W, Dimmable: No, Control: on/off.

Article data	
Article no.	17226000
GTIN	4251433913023
Short description	LED power supply 24V DC, on/off switchable
Material	Aluminium
Colour	White
Shape	Rectangular
Length	244 mm
Width	71 mm
Hight	38 mm
Weight	1.123 kg
Length of the connection line	300 mm
stamp	ENEC, MM
Conformance	CE

All technical data as well as, weight and measurements are based on rated values and had been carefully prepared. We reserve the right to make technical changes which are are important in progressing. Product pictures are examples and can vary from the original. Subject to errors. Date 22.10.2024 Orders are placed under our general terms and conditions under https://www.brumberg.com/en/terms-and-conditions/general-terms-and-conditions-of-sale/

LED power supply 24V DC, on/off switchable

Article no. 17226000

Light. For Generations.

Operating technology of driver	
AC nominal voltage min	200 V
AC nominal voltage max	305 V
Frequency min	47 Hz
Frequency max	63 Hz
DC nominal voltage min	142 V
DC nominal voltage max	431 V
Protection class	
Degree of protection	IP65
Power min	1 W
Power max.	240 W
Output_ripple_current	200
Starting current	60 A (510 µs)
Suitable for emergency lighting	No
measure point (tc)	90 °C
Power factor	0.95
max. no. lights on B16 A	4
max. no. lights on C16 A	6
Output voltage max	25.60 V
Output voltage min.	22.40 V
Control	on/off
Connection type-primary	Cable
Connection type-secondary	Open ends
Number of poles	3
Enviroment temprature (ta)	0°C up to 40°C
Measure point (tc)	max. +90 °C
Average nominal lifespan	100000 h
Output current	10 A mA
Length of the connection line	300 mm

Packing data	
Gross weight	1.177 kg
Length of packaging	300 mm
Packaging width	90 mm
Packaging hight	45 mm
Disposal at end of life	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately.
	By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.

All technical data as well as, weight and measurements are based on rated values and had been carefully prepared. We reserve the right to make technical changes which are are important in progressing. Product pictures are examples and can vary from the original. Subject to errors. Date 22.10.2024 Orders are placed under our general terms and conditions under https://www.brumberg.com/en/terms-and-conditions/general-terms-and-conditions-of-sale/

BRUMBERG