


## LED power supply 24 V DC, 1-10 V dimmable (analog)

Article no. 17206000







## Tondo

LED power supply unit 24 V DC, 1-10 V dimmable (analog), white, rectangular. This operating device meets the requirements for safety lighting systems in accordance with DIN EN 50172 VDE 0108-100:2005-01. This power supply unit is protected against overvoltage and short circuit as well as thermal and electrical overload by fuses. Material: Plastic, Protection class on room side: according to DIN EN 60529: IP20, Protection class: (EN 61140) II, Voltage: AC: 90-264 V, DC: 176-280 V, Power: 20 W, Dimmable: Yes, Type of dimming: 1-10 V.

Article data	
Article no.	17206000
GTIN	4250047767480
Short description	LED power supply 24 V DC, 1-10 V dimmable (analog)
Material	Plastic
Colour	White
Shape	Rectangular
Length	145 mm
Width	55 mm
Hight	19 mm
Weight	0.132 kg
stamp	ENEC 05, EL
Conformance	CE



## LED power supply 24 V DC, 1-10 V dimmable (analog)

Article no. 17206000

Operating technology of driver	
AC nominal voltage min	90 V
AC nominal voltage max	264 V
Frequency min	50 Hz
Frequency max	60 Hz
DC nominal voltage min	176 V
DC nominal voltage max	280 V
Protection class	
Degree of protection	IP20
Power min	1 W
Power	20 W
Starting current	27 A, 250 µs
Suitable for emergency lighting	No
measure point (tc)	80 °C
max. no. lights on B16 A	27
Output voltage max	24.00 V
Output voltage min.	24.00 V
Flicker value Pst LM	1.00
Control	1-10 V
Connection type-primary	Screw-in connection
Connection type-secondary	Screwed terminal
Number of poles	4
Enviroment temprature (ta)	0°C up to 40°C
Measure point (tc)	max. +80 °C

0.15 kg
60 mm
27 mm
150 mm
This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately.  By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.