


## LED power supply 24 V DC, on/off switchable

Article no. 17223000

Light.  
For Generations.



### Tender

LED power supply 24 V DC, on/off switchable, white, Rectangular. This power supply unit is equipped with safety devices which protect it against overvoltage, short-circuit as well as thermal and electric overloads. The input and output terminals are suitable for cables with a cross-section of up to 1.0 mm<sup>2</sup>. Material: Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, Voltage: 230V AC 50Hz, Power: 75 W, Control: on/off.

Article data	
Article no.	17223000
GTIN	4251433913047
Short description	LED power supply 24 V DC, on/off switchable
Material	Plastic
Colour	White
Shape	Rectangular
Length	185 mm
Width	60 mm
Height	31 mm
Weight	0.304 kg
stamp	MM
Conformance	CE

**LED power supply 24 V DC, on/off switchable**

Article no. 17223000

Light.  
For Generations.

Operating technology of driver	
AC nominal voltage min	198 V
AC nominal voltage max	264 V
Frequency min	50 Hz
Frequency max	60 Hz
Protection class	II
Degree of protection	IP20
Power min	1 W
Power	75 W
Starting current	
Suitable for emergency lighting	No
measure point (tc)	85 °C
Power factor	0.95
Output voltage max	24.00 V
Output voltage min.	24.00 V
Control	on/off
Connection type-primary	Screw-in connection
Connection type-secondary	Screwed terminal
Number of poles	2
Environment temperature (ta)	0°C up to 40°C
Measure point (tc)	max. +85 °C
Average nominal lifespan	50000 h

Packing data	
Gross weight	0.322 kg
Length of packaging	210 mm
Packaging width	65 mm
Packaging height	35 mm
Disposal at end of life	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.