

LED power supply 24 V DC, on/off switchable

Article no. 17207000

Light.
For Generations.

| Operating technology of driver | |
|---------------------------------|---------------------|
| AC nominal voltage min | 100 V |
| AC nominal voltage max | 240 V |
| Frequency min | 50 Hz |
| Frequency max | 60 Hz |
| Protection class | II |
| Degree of protection | IP20 |
| Power min | 1 W |
| Power max. | 30 W |
| Starting current | 35 A, 100us |
| Suitable for emergency lighting | No |
| measure point (tc) | 85 °C |
| Power factor | 0.95 |
| Output voltage max | 24.00 V |
| Output voltage min. | 24.00 V |
| Control | on/off |
| Connection type-primary | Screw-in connection |
| Connection type-secondary | Screwed terminal |
| Number of poles | 2 |
| Environment temperature (ta) | 0°C up to 40°C |
| Measure point (tc) | max. +85 °C |
| Average nominal lifespan | 50000 h |

| Packing data | |
|-------------------------|---|
| Gross weight | 0.172 kg |
| Length of packaging | 60 mm |
| Packaging width | 30 mm |
| Packaging height | 165 mm |
| Disposal at end of life | This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment. |