
BRUMBERG

LED surface-mounted spot, 27W

Article no. 89126030

Light. For Generations.













LED surface-mounted spot, 27W, Round. Ceiling cut-out Installation depth mm, Outer diameter 126 mm, Weight 2,332 kg, with rotattionssymmetrical, deep, wide distributed light intensity. Luminous flux 2.704 lm, Power 1 x 27 W, Light colour warm white, Correlated color temprature (CCT) 3.000 K, Colour rendering index CRI > 80, Housing material: Aluminium, Colour: Black, Permissible ambient temperature (ta): -20 °C - +25 °C, Protection class (EN 61140): I, Degree of protection (DIN EN 60529): IP20, .With electronic driver, on/off switchable.

| Article data | |
|-------------------|-------------------------------|
| Article no. | 89126030 |
| GTIN | 4251433901662 |
| Short description | LED surface-mounted spot, 27W |
| Material | Aluminium |
| Colour | Black |
| Type of surface | Matt |
| Shape | Round |
| Outer diameter | 126 mm |
| Hight | 284 mm |
| Weight | 2.332 kg |

BRUMBERG

LED surface-mounted spot, 27W

Article no. 89126030

Light. For Generations.

| Lighting technology | |
|------------------------------|------------|
| Colour temperature | 3.000 K |
| Light colour | White |
| Luminous flux | 2,704 lm |
| System efficiency | 100 lm/W |
| Colour rendering | CRI > 80 |
| Reflector | High-gloss |
| Beam angle | 24° |
| Light sharing | Symmetric |
| Adjustable color temperature | No |

| Operating technology of the luminaire | |
|---------------------------------------|--|
| System output | 27 W |
| Voltage type | AC |
| AC nominal voltage max | 230 V |
| Frequenz max. | 50 Hz |
| Lamp | LED |
| Protection class | |
| Degree of protection | IP20 |
| Control | on/off |
| Bulb change possible | The light source of this luminaire may only be replaced by the manufacturer or a service technician commissioned by him or a similarly qualified person. |

| Mounting technology | |
|-----------------------------|-------------------------------|
| Mounting method | Surface mounting |
| Place of installation | Ceiling-mounted |
| Adjustability | Rotatable and adjustable head |
| Swivel angle | 180° |
| Rotation angle | 355° |
| Head adjustable angle | 180° |
| Suitable for through-wiring | No |

| Packing data | |
|-------------------------|--|
| Gross weight | 2.954 kg |
| Length of packaging | 280 mm |
| Packaging width | 200 mm |
| Packaging hight | 280 mm |
| | This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. |
| Disposal at end of life | By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment. |