
## BRUMBERG

## LED converter 350 mA, 1-10 V dimmable (analog)

Article no. 17657010

Light. For Generations.







## Tender

LED converter 350 mA, 1-10 V dimmable (analog), white, Rectangular. This converter is equipped with safety devices which protect it against overvoltage, short-circuit as well as thermal and electric overloads. The input and output terminals are suitable for cables with a cross-section of up to 1.5 mm<sup>2</sup>. Material: Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, Current: 350 mA, Voltage: 230V AC 50Hz , Power: 18 W, Dimmable: Yes, Control: 1-10 V.

| Article data      |  |
|-------------------|--|
| Article no.       | 17657010                                       |
| GTIN              | 4251433923961                                  |
| Short description | LED converter 350 mA, 1-10 V dimmable (analog) |
| Material          | Plastic  |
| Colour            | White  |
| Shape             | Rectangular                                    |
| Length            | 110 mm   |
| Width             | 52 mm  |
| Hight             | 22 mm  |
| Weight            | 0.108 kg                                       |
| stamp             | ENEC 05, MM, EL                                |
| Conformance       | CE   |

All technical data as well as, weight and measurements are based on rated values and had been carefully prepared. We reserve the right to make technical changes which are are important in progressing. Product pictures are examples and can vary from the original. Subject to errors. Date 22.10.2024 Orders are placed under our general terms and conditions under https://www.brumberg.com/en/terms-and-conditions/general-terms-and-conditions-of-sale/

## LED converter 350 mA, 1-10 V dimmable (analog)

Article no. 17657010

Light. For Generations.

**BRUMBERG** 

| Operating technology of driver  |                     |
|---------------------------------|---------------------|
| AC nominal voltage min          | 99 V                |
| AC nominal voltage max          | 264 V               |
| Frequency min                   | 50 Hz               |
| Frequency max                   | 60 Hz               |
| DC nominal voltage min          | 176 V               |
| DC nominal voltage max          | 280 V               |
| Protection class                | II                  |
| Degree of protection            | IP20                |
| Power min                       | 5.2 W               |
| Power                           | 18 W                |
| Output_ripple_current           | 3                   |
| Starting current                | 5A 50µs             |
| Suitable for emergency lighting | No                  |
| measure point (tc)              | 2° 08               |
| Version                         | without             |
| Power factor                    | 0.95                |
| max. no. lights on B16 A        | 50                  |
| Output voltage max              | 50.00 V             |
| Output voltage min.             | 15.00 V             |
| Flicker value Pst LM            | 1.00                |
| Control                         | 1-10 V              |
| Number of poles                 | 4                   |
| Enviroment temprature (ta)      | -25 °C up to +50 °C |
| Measure point (tc)              | max. +80 °C         |
| Output current                  | 350 mA              |

| Packing data            |  |
|-------------------------|--|
| Gross weight            | 0.126 kg   |
| Length of packaging     | 60 mm  |
| Packaging width         | 27 mm  |
| Packaging hight         | 150 mm   |
| Disposal at end of life | This product must not be disposed of with household waste. You are obliged, to dispose of<br>such electrical waste separately.<br>By disposing of electrical waste and other old or defective electronics separately, you<br>support recycling or other forms of re-use. In that way you help to take care and to avoid that |
|                         | harmful substances get into the environment.   |

All technical data as well as, weight and measurements are based on rated values and had been carefully prepared. We reserve the right to make technical changes which are are important in progressing. Product pictures are examples and can vary from the original. Subject to errors. Date 22.10.2024 Orders are placed under our general terms and conditions under https://www.brumberg.com/en/terms-and-conditions/general-terms-and-conditions-of-sale/