
# **BRUMBERG**

### LED converter 700 mA, DALI dimmable (digital)

Article no. 17788010

Light. For Generations.







#### Tender

LED converter 700 mA, DALI dimmable (digital), white, Rectangular. This converter is equipped with safety devices which protect it against overvoltage, short-circuit as well as thermal and electric overloads. The input and output terminals are suitable for cables with a cross-section of up to 0.75-1.5 mm². Material: Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, Current: 700 mA, Voltage: 230V AC 50Hz, Power: 38 W, Dimmable: Yes, Control: DALI-2.

Article data	
Article no.	17788010
GTIN	4251433924180
Short description	LED converter 700 mA, DALI dimmable (digital)
Material	Plastic
Colour	White
Shape	Rectangular
Length	146 mm
Width	44 mm
Hight	30 mm
Weight	0.153 kg
stamp	ENEC 05, MM, EL

# **BRUMBERG**

## LED converter 700 mA, DALI dimmable (digital)

Article no. 17788010

Light. For Generations.

Operating technology of driver	
AC nominal voltage min	198 V
AC nominal voltage max	264 V
Frequency min	50 Hz
Frequency max	60 Hz
DC nominal voltage min	176 V
DC nominal voltage max	275 V
Protection class	
Degree of protection	IP20
Power min	7 W
Power	38 W
Output_ripple_current	3
Starting current	5A 50μs
Suitable for emergency lighting	No
measure point (tc)	85 °C
Version	without
Power factor	0.95
Output voltage max	54.00 V
Output voltage min.	10.00 V
Control	DALI-2
Number of poles	4
Enviroment temprature (ta)	-25 °C up to +45 °C
Measure point (tc)	85 °C
Output current	700 mA

Packing data	
Gross weight	0.173 kg
Length of packaging	45 mm
Packaging width	35 mm
Packaging hight	190 mm
Disposal at end of life	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately.  By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.