

BRUMBERG

LED converter 350 mA, trailing-edge phase dimmable

Article no. 17664010

Light. For Generations.







Tender

LED converter 350 mA, trailing-edge phase dimmable, white, Rectangular. This converter is equipped with safety devices which protect it against overvoltage, short-circuit as well as thermal and electric overloads. The input and output terminals are suitable for cables with a cross-section of up to 1.5 mm². Material: Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, Voltage: 230V AC 50Hz, Power: 14 W, Dimmable: Yes, Control: Trailing-edge phase.

Article data	
Article no.	17664010
GTIN	4251433919490
Short description	LED converter 350 mA, trailing-edge phase dimmable
Material	Plastic
Colour	White
Shape	Rectangular
Length	125 mm
Width	51 mm
Hight	20 mm
Weight	0.065 kg
stamp	ENEC 05
Conformance	CE

All technical data as well as, weight and measurements are based on rated values and had been carefully prepared. We reserve the right to make technical changes which are are important in progressing. Product pictures are examples and can vary from the original. Subject to errors. Date 22.10.2024 Orders are placed under our general terms and conditions under https://www.brumberg.com/en/terms-and-conditions/general-terms-and-conditions-of-sale/

LED converter 350 mA, trailing-edge phase dimmable

Article no. 17664010

Light. For Generations.

BRUMBERG

Operating technology of driver	
AC nominal voltage min	198 V
AC nominal voltage max	264 V
Frequency min	50 Hz
Frequency max	60 Hz
Protection class	I
Degree of protection	IP20
Power min	10.2 W
Power max.	14 W
Output_ripple_current	15
Starting current	1.87A 48µs
Suitable for emergency lighting	No
measure point (tc)	80 °C
Version	without
Power factor	0.9
max. no. lights on B16 A	155
Output voltage max	40.00 V
Output voltage min.	29.00 V
Control	Trailing-edge phase
Number of poles	2
Enviroment temprature (ta)	0°C up to 40°C
Measure point (tc)	max. +80 °C
Average nominal lifespan	50000 h
Output current	350 mA

Packing data	
Gross weight	0.089 kg
Length of packaging	60 mm
Packaging width	30 mm
Packaging hight	165 mm
Disposal at end of life	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that
	harmful substances get into the environment.