BRUMBERG

RGBW radio control

Article no. 18220000

Light. For Generations.







Tender

RGBW radio control.RGBW radio controller for controlling the RGBW LED modules for color and white light. Voltage: 12-24 V DC, Current: maximum 4 x 2.5 A. Power: maximum 240 W / 480 W (12 V DC / 24 V DC). Control: negative (common anode). Control signal: PWM. Radio frequency: 869.5 MHz. Range (visual contact): up to 20 m. Ambient temperature (ta): 0 °C to +40 °C. Controller connection using screw terminals. Dimensions: L 178 x W 46 x H 18 mm. Material: Plastic. Delivery: including strain relief. Controller per remote control: maximum 4 (for optimum radio connection). Remote control: voltage (battery): 4.5 V DC - 3 x AAA (not included in the scope of delivery). Radio frequency: 869.5 MHz, transmission power (Ps) < 0 dBm, Range (visual contact): up to 20 m. Ambient temperature (ta): 0 °C to +40 °C. Dimensions: L 120 x W 48 x H 18 mm. Material: Plastic. Function scope:- On / Off. White light selection key (ww / nw / w). RGB color change using a touch wheel. Dimmer keys for red / green / blue / white- Dimming of the set light color. Save keys S1 / S2. Color gradient: Start / Stop. Color gradient: Speed Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Voltage: 12V 24V, Power: 240 W, Control: Wireless technology control.

Article data	
Article no.	18220000
GTIN	4251433922377
Short description	RGBW radio control
Material	Plastic
Length	145 mm
Width	46.5 mm
Hight	16 mm
Weight	0.071 kg

All technical data as well as, weight and measurements are based on rated values and had been carefully prepared. We reserve the right to make technical changes which are are important in progressing. Product pictures are examples and can vary from the original. Subject to errors.

Date 10.04.2024 Orders are placed under our general terms and conditions under https://www.brumberg.com/en/terms-and-conditions/general-terms-and-conditions-of-sale/

RGBW radio control

Article no. 18220000

Light. For Generations.

Packing data	
Gross weight	0.089 kg
Length of packaging	150 mm
Packaging width	50 mm
Packaging hight	25 mm
Disposal at end of life	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. By disposing of electrical waste and other old or defective electronics separately, you
	support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.