



QUALITYFLEX Select HE LED flex lighting, 5 m, CRI > 90, 4,8 W / m, IP00

Article no. 75501004







Tender

LED flex board, 125 mm, CRI > 90, 4.8 W / m, IP00, LED white light, 4,000K, CRI > 90 LED flex board, length: 125.0 mm Lamp wattage per meter: 4.8 W/m, luminous flux per meter: 779.0 lm/m, degree of protection on room side: IP00, protection class: III, voltage: 24V DC, beam angle: $120.0 ^{\circ}$, 64 LEDs per meter, chip spacing (short pitch): 15.62 mm. The LED flex board can be shortened every 125 mm for individual applications. The maximum system length of 5,000 mm must not be exceeded with one feed.

Product Benefits

- Suitable for indoor use (IP00).
- 8 LEDs per segment.
- Decorative lighting of furniture, objects and light coves.
- Length 5,000 mm with a pitch of 125 mm.
- Lifetime L80/B10: 123,000 hours.
- $\bullet\,$ Optimal heat dissipation due to matching aluminum profiles.
- Dimmable with appropriate accessories.



QUALITYFLEX Select HE LED flex lighting, 5 m, CRI > 90, 4.8 W / m, IP00

Article no. 75501004

Article data	
Article no.	75501004
GTIN	4251433957034
Series name	QUALITYFLEX Select HE
Short description	LED flex lighting, 5 m, CRI > 90, 4,8 W / m, IP00
Colour	White
Length	125 mm
Width	8 mm
Hight	1.4 mm
Scope of delivery	incl. 1 x mounting instructions, 5 x identification labels
Weight	0.003 kg
Length of the connection line	350 mm
Conformance	CE, UKCA

Lighting technology	
Colour temperature	4.000 K
Light colour	White
Luminous flux per meter	779 lm/m
System efficiency	162 lm/W
McAdam-Step	McAdam-Step 3
Colour rendering	CRI > 90
Beam angle	120°
Adjustable color temperature	No

Operating technology of the luminaire					
System output	24 W				
Lamp power per meter	4.8 W/m				
Voltage type	DC				
DC nominal voltage max	24 V				
Lamp	LED				
Protection class					
Degree of protection	IP00				
Ambient temperature	-10 °C up to +40 °C				
Dimmable	Yes				
Wire number	2				
Control	Depending on driver				
Length of the connection line	350 mm				
Cable assignment	red = + pole				
Cable assignment	black = - pole				
Design of the connecting cable	one-sided				
Bulb change possible	No				
Rated life time L70/B50 at 25 °C	181,000 h				
Rated life time L80/B10 at 25 °C	123.000 h				
Energy efficiency class	C				

Operating technology of QualityFlex	
Power per meter	4.8 W/m
Short Pitch	15.62 mm
Number of lamps per meter	64 Qty
Length of individual sections	125 mm
Smallest bend radius	30 mm
Length	125 mm
Maximum module length	5,000 mm
Circuit type	Parallel conduction
LED Type	2835 LED



QUALITYFLEX Select HE LED flex lighting, 5 m, CRI > 90, 4.8 W / m, IP00

Article no. 75501004

Packing data	
Gross weight	0.007 kg
Length of packaging	70 mm
Packaging width	45 mm
Packaging hight	80 mm
	This product must not be disposed of with household waste. You are obliged, to dispose of
	such electrical waste separately.
Disposal at end of life	By disposing of electrical waste and other old or defective electronics separately, you
	support recycling or other forms of re-use. In that way you help to take care and to avoid that
	harmful substances get into the environment.

Compatible Driver						
Article no.	Power min	Power	Control	Length	Width	Hight
17206000	1 W	20 W	1-10 V	146 mm	55 mm	19 mm
17207000	1 W	30 W	on/off	160 mm	50 mm	22 mm
17214000	1 W	7.2 W	on/off	68 mm	35 mm	21 mm
17223000	1 W	75 W	on/off	185 mm	60 mm	31 mm
17224000	1 W	100 W	on/off	199 mm	63 mm	36 mm
17225000	1 W	150 W	on/off	219 mm	63 mm	36 mm
17226000	1 W	240 W	on/off	244 mm	71 mm	38 mm
17227000	1 W	320 W	on/off	252 mm	90 mm	44 mm
17228000	1 W	480 W	on/off	262 mm	125 mm	44 mm
17230000	5 W	30 W	Trailing-edge phase	145 mm	50 mm	22 mm
17231000	12 W	75 W	Trailing-edge phase	185 mm	60 mm	31 mm
17232000	12 W	120 W	Trailing-edge phase	223 mm	64 mm	32 mm
17240000	1 W	20 W	on/off	150 mm	40 mm	30 mm
17241000	1 W	40 W	on/off	210 mm	40 mm	30 mm
17242000	1 W	60 W	on/off	250 mm	40 mm	30 mm
17243000	1 W	120 W	on/off	300 mm	40 mm	30 mm
17244000	1 W	150 W	on/off	310 mm	40 mm	30 mm
17250000	1 W	45 W	DALI-2	187 mm	45 mm	31 mm
17251000	1 W	80 W	DALI-2	290 mm	45 mm	31 mm
17252000	1 W	150 W	DALI-2	290 mm	45 mm	31 mm
17260000	1 W	150 W	on/off	105 mm	90 mm	59 mm

Compatible Conroller						
Article no.	Power min	Power	Control	Length	Width	Hight
17502000	1 W	120 W	DALI	183 mm	33 mm	23 mm
18151000	1 W	240 W	KNX	170 mm	59 mm	30 mm
18152000	1 W	240 W	DALI-DT6	170 mm	59 mm	30 mm
18153000	1 W	240 W	DMX	170 mm	59 mm	30 mm
18154000	1 W	240 W	1-10 V	170 mm	59 mm	30 mm
18161000	1 W	240 W	KNX	72 mm	90 mm	70 mm
18162000	1 W	240 W	DALI-DT6	54 mm	110 mm	66 mm
18164000	1 W	240 W	1-10 V	54 mm	110 mm	66 mm
17528000	1 W	240 W	Wireless technology control			
17511000	1 W	240 W	Wireless technology control	145 mm	46.5 mm	16 mm
18157000	1 W	240 W	ZigBee	145 mm	46.5 mm	16 mm
18192000	1 W	240 W	Wireless technology control	160 mm	45 mm	18 mm



QUALITYFLEX Select HE LED flex lighting, 5 m, CRI > 90, 4.8 W / m, IP00

Article no. 75501004

Compatible Profiles				
Short description	Series name	Length	Width	Hight
Recessed profile	P36-20	2 000 mm	30 mm	20.4 mm
53654070	P30-20	2,000 mm	30 111111	20.4 mm
LED recessed profile	P40-30	2,000 mm	44.4 mm	24 mm
53759070	F 40-30	2,000 111111	44.4 111111	24 111111
Wall recessed profile	P32-12	2,000 mm	19.1 mm	81 mm
53650260	102 12	2,000 11111	17.1111111	01111111
Plaster profile	P37-30	2,000 mm	63.4 mm	15.9 mm
53655070		2,000		
Plaster profile	P38-30	2,000 mm	63.4 mm	24 mm
53656070		,		
Surface-mounted profile	P01-10	2,000 mm	20 mm	8 mm
53600070				
Surface-mounted profile	P04-14	2,000 mm	24 mm	9 mm
53602070				
Surface-mounted profile	P05-14	2,000 mm	17.5 mm	8.6 mm
53604080				
Surface-mounted profile 53603070	P06-20	2,000 mm	23 mm	25.1 mm
LED surface-mounted profile				
53606070	P30-30	2,000 mm	33.4 mm	29.6 mm
Surface-mounted profile				
53607080	P16-16	2,000 mm	18.8 mm	18.6 mm
Surface-mounted profile, flat				
53380261	ONE		17.6 mm	6 mm
Surface-mounted profile, high				
53381302	ONE		17.6 mm	15.9 mm
Surface-mounted corner profile				
53700070	P60-10	2,000 mm	20 mm	16 mm
Surface-mounted corner profile				
53702070	P62-14	2,000 mm	24 mm	19.4 mm
Surface-mounted corner profile				
53703260	P63-14	2,000 mm	17.5 mm	17.5 mm
Surface-mounted corner profile	ONE		0.4	10.4
53385261	ONE		24 mm	19.4 mm
Flexible profile	D70 10	2 000	20	2.2
53753260	P72-12	2,000 mm	20 mm	3.3 mm
Wall surface-mounted profile	D70 10	2 000	17.0	46 1
53754070	P73-12	2,000 mm	17.8 mm	46.1 mm
Wall surface-mounted profile	P74-14	2 000 mm	10 5 mm	55 mm
53751260	r/4-14	2,000 mm	18.5 mm	55 mm
Flat profile P76-16	P76-16	2,000 mm	20.5 mm	3.8 mm
53756070	F/0-10	2,000 111111	20.3 11111	3.0 111111
Surface-mounted round profile	P90-16	2,000 mm	20 mm	17.04 mm
53760260	1. 30-10	2,000 11111	20 111111	17.04