




QUALITYFLEX Performance LED flex lighting, 20 m, CRI > 95, 5,0 W / m, IP00

Article no. 19302204

Light.
For Generations.**Tender**

LED flex lighting, 20 m, CRI > 95, 5,0 W / m, IP00, white, 4.000K, CRI > 95. LED flex lighting decorative, technical as well as efficient lighting of light coves, linear applications and backlighting, basic or general lighting of rooms, architectural applications and for areas where high illumination is required, such as indirect or direct lighting, luminous ceilings, gastronomy lighting and much more. Length: 20000.0 mm Lamp power per meter: 5.0 W/m, Luminous flux per meter: 455.0 lm/m, Degree of protection: IP00, Protection class: III, Voltage: 24V DC, Beam angle: 120.0 °, 60 LEDs per meter, Chip distance (Short Pitch) : 16,7mm. For individual application, the LED flex board can be used all 100 mm be cut back. The maximum system length of 20.000mm must not be exceeded with one feed-in.

Product Benefits

- Very high colour rendering with CRI>95.
- Length of 20 meters can be realized with one feed-in.
- Ideal for decorative lighting and backlighting of furniture and furnishings.
- Indirect lighting in the living area.
- Suitable for use in dry indoor areas (IP00).
- Very long service life time of 50,000 hours.
- Dimmable with appropriate accessories.

QUALITYFLEX Performance LED flex lighting, 20 m, CRI > 95, 5,0 W / m, IP00

Article no. 19302204

Light.
For Generations.

| Article data | |
|-------------------------------|--|
| Article no. | 19302204 |
| GTIN | 4251433927570 |
| Series name | QUALITYFLEX Performance |
| Short description | LED flex lighting, 20 m, CRI > 95, 5,0 W / m, IP00 |
| Colour | White |
| Length | 20,000 mm |
| Width | 10 mm |
| Hight | 1.4 mm |
| Scope of delivery | incl. 1 x mounting instructions, 5 x identification labels |
| Weight | 0.472 kg |
| Length of the connection line | 350 mm |
| Conformance | CE, UKCA |

| Lighting technology | |
|------------------------------|---------------|
| Colour temperature | 4.000 K |
| Light colour | White |
| Luminous flux per meter | 455 lm/m |
| System efficiency | 91 lm/W |
| McAdam-Step | McAdam-Step 5 |
| Colour rendering | CRI > 95 |
| Beam angle | 120° |
| Adjustable color temperature | No |

| Operating technology of the luminaire | |
|---------------------------------------|--------------------------------|
| System output | 100 W |
| Lamp power per meter | 5 W/m |
| Voltage type | DC |
| DC nominal voltage max | 24 V |
| Lamp | LED |
| Protection class | III |
| Degree of protection | IP00 |
| Ambient temperature | -10 °C up to +40 °C |
| Dimmable | Yes |
| Wire number | 2 |
| Control | Depending on driver |
| Length of the connection line | 350 mm |
| Cable assignment | rot = + pol schwarz = - pol |
| Design of the connecting cable | both sides |
| Bulb change possible | No |
| Energy efficiency class | F |

| Operating technology of QualityFlex | |
|-------------------------------------|---------------------|
| Power per meter | 5 W/m |
| Short Pitch | 16.7 mm |
| Number of lamps per meter | 60 Qty |
| Length of individual sections | 100 mm |
| Smallest bend radius | 25 mm |
| Length | 20,000 mm |
| Maximum module length | 20,000 mm |
| Circuit type | Parallel conduction |
| LED Type | 2835 LED |

QUALITYFLEX Performance LED flex lighting, 20 m, CRI > 95, 5,0 W / m, IP00

Article no. 19302204

Light.
For Generations.

| Packing data | |
|-------------------------|--|
| Gross weight | 0.518 kg |
| Length of packaging | 335 mm |
| Packaging width | 335 mm |
| Packaging height | 18 mm |
| Disposal at end of life | <p>This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately.</p> <p>By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.</p> |

| Compatible Driver | | | | | | |
|-------------------|-----------|-------|---------------------|--------|--------|-------|
| Article no. | Power min | Power | Control | Length | Width | Hight |
| 17206000 | 1 W | 20 W | 1-10 V | 146 mm | 55 mm | 19 mm |
| 17207000 | 1 W | 30 W | on/off | 160 mm | 50 mm | 22 mm |
| 17214000 | 1 W | 7.2 W | on/off | 68 mm | 35 mm | 21 mm |
| 17223000 | 1 W | 75 W | on/off | 185 mm | 60 mm | 31 mm |
| 17224000 | 1 W | 100 W | on/off | 199 mm | 63 mm | 36 mm |
| 17225000 | 1 W | 150 W | on/off | 219 mm | 63 mm | 36 mm |
| 17226000 | 1 W | 240 W | on/off | 244 mm | 71 mm | 38 mm |
| 17227000 | 1 W | 320 W | on/off | 252 mm | 90 mm | 44 mm |
| 17228000 | 1 W | 480 W | on/off | 262 mm | 125 mm | 44 mm |
| 17230000 | 5 W | 30 W | Trailing-edge phase | 145 mm | 50 mm | 22 mm |
| 17231000 | 12 W | 75 W | Trailing-edge phase | 185 mm | 60 mm | 31 mm |
| 17232000 | 12 W | 120 W | Trailing-edge phase | 223 mm | 64 mm | 32 mm |
| 17240000 | 1 W | 20 W | on/off | 150 mm | 40 mm | 30 mm |
| 17241000 | 1 W | 40 W | on/off | 210 mm | 40 mm | 30 mm |
| 17242000 | 1 W | 60 W | on/off | 250 mm | 40 mm | 30 mm |
| 17243000 | 1 W | 120 W | on/off | 300 mm | 40 mm | 30 mm |
| 17244000 | 1 W | 150 W | on/off | 310 mm | 40 mm | 30 mm |
| 17250000 | 1 W | 45 W | DALI-2 | 187 mm | 45 mm | 31 mm |
| 17251000 | 1 W | 80 W | DALI-2 | 290 mm | 45 mm | 31 mm |
| 17252000 | 1 W | 150 W | DALI-2 | 290 mm | 45 mm | 31 mm |
| 17260000 | 1 W | 150 W | on/off | 105 mm | 90 mm | 59 mm |

| Compatible Controller | | | | | | |
|-----------------------|-----------|-------|-----------------------------|--------|---------|-------|
| Article no. | Power min | Power | Control | Length | Width | Hight |
| 18151000 | 1 W | 240 W | KNX | 170 mm | 59 mm | 30 mm |
| 18152000 | 1 W | 240 W | DALI-DT6 | 170 mm | 59 mm | 30 mm |
| 18153000 | 1 W | 240 W | DMX | 170 mm | 59 mm | 30 mm |
| 18154000 | 1 W | 240 W | 1-10 V | 170 mm | 59 mm | 30 mm |
| 18161000 | 1 W | 240 W | KNX | 72 mm | 90 mm | 70 mm |
| 18162000 | 1 W | 240 W | DALI-DT6 | 54 mm | 110 mm | 66 mm |
| 18164000 | 1 W | 240 W | 1-10 V | 54 mm | 110 mm | 66 mm |
| 17528000 | 1 W | 240 W | Wireless technology control | | | |
| 17502000 | 1 W | 120 W | DALI | 183 mm | 33 mm | 23 mm |
| 18157000 | 1 W | 240 W | ZigBee | 145 mm | 46.5 mm | 16 mm |
| 18192000 | 1 W | 240 W | Wireless technology control | 160 mm | 45 mm | 18 mm |
| 18207000 | | | | 137 mm | 45 mm | 13 mm |
| 18199000 | | | | | | |
| 18202000 | | | | | | |

QUALITYFLEX Performance LED flex lighting, 20 m, CRI > 95, 5,0 W / m, IP00

Article no. 19302204

Light.
For Generations.

| Compatible Profiles | | | | |
|--|-------------|----------|---------|---------|
| Short description | Series name | Length | Width | Hight |
| Recessed profile 53654070 | P36-20 | 2,000 mm | 30 mm | 20.4 mm |
| LED recessed profile 53759070 | P40-30 | 2,000 mm | 44.4 mm | 24 mm |
| Wall recessed profile 53650260 | P32-12 | 2,000 mm | 19.1 mm | 81 mm |
| Plaster profile 53655070 | P37-30 | 2,000 mm | 63.4 mm | 15.9 mm |
| Plaster profile 53656070 | P38-30 | 2,000 mm | 63.4 mm | 24 mm |
| Surface-mounted profile 53600070 | P01-10 | 2,000 mm | 20 mm | 8 mm |
| Surface-mounted profile 53602070 | P04-14 | 2,000 mm | 24 mm | 9 mm |
| Surface-mounted profile 53604080 | P05-14 | 2,000 mm | 17.5 mm | 8.6 mm |
| Surface-mounted profile 53603070 | P06-20 | 2,000 mm | 23 mm | 25.1 mm |
| LED surface-mounted profile 53606070 | P30-30 | 2,000 mm | 33.4 mm | 29.6 mm |
| Surface-mounted profile 53607080 | P16-16 | 2,000 mm | 18.8 mm | 18.6 mm |
| Surface-mounted profile, flat 53380261 | ONE | | 17.6 mm | 6 mm |
| Surface-mounted profile, high 53381302 | ONE | | 17.6 mm | 15.9 mm |
| Surface-mounted corner profile 53700070 | P60-10 | 2,000 mm | 20 mm | 16 mm |
| Surface-mounted corner profile 53702070 | P62-14 | 2,000 mm | 24 mm | 19.4 mm |
| Surface-mounted corner profile 53703260 | P63-14 | 2,000 mm | 17.5 mm | 17.5 mm |
| Surface-mounted corner profile 53385261 | ONE | | 24 mm | 19.4 mm |
| Flexible profile 53753260 | P72-12 | 2,000 mm | 20 mm | 3.3 mm |
| Wall surface-mounted profile 53754070 | P73-12 | 2,000 mm | 17.8 mm | 46.1 mm |
| Wall surface-mounted profile 53751260 | P74-14 | 2,000 mm | 18.5 mm | 55 mm |
| Flat profile P76-16 53756070 | P76-16 | 2,000 mm | 20.5 mm | 3.8 mm |
| Surface-mounted round profile 53760260 | P90-16 | 2,000 mm | 20 mm | 17 mm |