
CORBET-S Einbaustrahler, GU10

Article no. 36305150







Tender

Recessed spotlight, GU10, matt nickel, square. Designed in a compact shape for quick, tool-free installation in the ceiling. Incl. bracket with GU10 socket for standard-compliant strain relief. Version: GU10, Mounting type: recessed mounting, Mounting location: ceiling mounting, Material: steel, Protection rating on room side: to DIN EN 60529: IP20, Protection class: (EN 61140) II, Voltage: 230V AC 50Hz, Power: 10 W, Number of bulbs / sockets: 1 piece, Adjustability: swivel, without control gear, Type of dimming: other.

Product Benefits

- Einbaustrahler in quadratischer Bauform aus Stahl für LED-Retrofit-Lampen mit Sockel GU10.
- Inkl. Bügel zur normgerechten Zugentlastung.
- Deckenausschnitt 68 mm, Länge 82 mm, Breite 82 mm, Einbautiefe 125 mm, IP20.
- Schwenkbereich 25°.
- Ausführung: mit Sprengring.
- Klassische, formal zurückgenommene Formgebung.
- In gleicher Optik auch als GX5,3-Ausführung, als schaltbares und dimmbares Set (Phasenabschnitt) lieferbar.
- Zudem in gleicher Oberflächenstruktur und in gleichen Farben auch in Ausführung rund verfügbar.



CORBET-S Einbaustrahler, GU10

Article no. 36305150

| Article data | |
|--------------------|----------------------|
| Article no. | 36305150 |
| GTIN | 4250047782469 |
| Series name | CORBET-S |
| Short description | Einbaustrahler, GU10 |
| Material | Steel |
| Colour | Nickel |
| Type of surface | Matt |
| Shape | Square |
| Length | 82 mm |
| Width | 82 mm |
| Built-in diameter | 68 mm |
| Installation depth | 125 mm |
| Hight | 3 mm |
| Weight | 0.139 kg |
| Conformance | CE, UKCA |

| Operating technology of the luminaire | |
|---------------------------------------|------------------------|
| System output | 10 W |
| Voltage type | AC |
| AC nominal voltage max | 230 V |
| Frequency max | 50 Hz |
| Lamp | For LED-retrofill lamp |
| Lamp holder | GU10 |
| Protection class | П |
| Degree of protection | IP20 |
| Control | Other |
| Bulb change possible | Yes |
| Energy efficiency class | nicht erforderlich |

| Mounting technology | |
|------------------------|---|
| Mounting method | Recessed mounting |
| Place of installation | Ceiling-mounted |
| Adjustability | Pivoted |
| Swivel angle | 25° |
| Max. ceiling thickness | 13 mm |
| Further references | No cover with thermal insulation material |
| Material cover | Without cover |

| Packing data | |
|-------------------------|--|
| Gross weight | 0.199 kg |
| Length of packaging | 140 mm |
| Packaging width | 110 mm |
| Packaging hight | 120 mm |
| | This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. |
| Disposal at end of life | By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment. |

All technical data as well as, weight and measurements are based on rated values and had been carefully prepared. We reserve the right to make technical changes which are are important in progressing. Product pictures are examples and can vary from the original. Subject to errors. Date 07.05.2025 Orders are placed under our general terms and conditions under https://www.brumberg.com/en/terms-and-conditions/general-terms-and-conditions-of-sale/