
## MELODY LED floor luminaire, NANO prismatic cover, with indirect light component Article no. 77422174AI





**BRUMBERG** 

Light. Since 1873.

₩ 15,200lm	230V	

## Tender

Rectangular LED free-standing luminaire, NANO prismatic cover, with indirect component, height 2,050 mm, luminaire length 1,282 mm, luminaire width 210 mm, height 2,050 mm, weight 17.400 kg, double asymmetrical cover plastic microprismatic, rated luminous flux 15.200 Im, UGR < 19, rated wattage 120 W, neutral white light color, most similar color temperature (CCT) 4,000 K, general color rendering index CRI > 90, housing material: aluminum / steel / plastic, color: white, permissible ambient temperature (ta): -20 °C - +25 °C, protection class (EN 61140): I, degree of protection (DIN EN 60529): IP20. With electronic control gear, Casambi, presence detector, daylight sensor, app, dimmable push-button.

Article data	
Article no.	77422174AI
GTIN	4251433970590
Series name	MELODY
Short description	LED floor luminaire, NANO prismatic cover, with indirect light component
Material	Aluminium / Steel / Plastic
Colour	White
Type of surface	Structure
Shape	Rectangular
Length	1,282 mm
Width	210 mm
Hight	2,050 mm
Scope of delivery	incl. supply line 2.500 mm with Schuko angle plug
Weight	17.400 kg
Conformance	CE

All technical data as well as, weight and measurements are based on rated values and had been carefully prepared. We reserve the right to make technical changes which

are are important in progressing. Product pictures are examples and can vary from the original. Subject to errors. Date 08.04.2025 Orders are placed under our general terms and conditions under https://www.brumberg.com/en/terms-and-conditions/general-terms-and-conditions-of-sale/

## MELODY LED floor luminaire, NANO prismatic cover, with indirect light component Article no. 77422174Al

Lighting technology		
Colour temperature	4.000 K	
Light colour	White	
Light output	Direct/Indirect	
Luminous flux	15,200 lm	
Luminous flux component (direct / indirect)	16/84 %	
System efficiency	127 lm/W	
McAdam-Step	McAdam-Step 3	
Colour rendering	CRI > 90	
Glare evaluation	UGR < 19	
Luminance < 3,000 cd/m <sup>2</sup> above 65° beam	Yes	
angle	162	
Light sharing	Double asymmetric	
Adjustable color temperature	No	

Operating technology of the luminaire	
System output	120 W
Voltage type	AC
AC nominal voltage max	230 V
Frequency max	50 Hz
Lamp	LED
Lamp holder	Without fitting
Protection class	I
Degree of protection	IP20
Control	Casambi, Presence detector, Daylight detector, App, Button
Pulh change peopible	The light source of this luminaire may only be replaced by the manufacturer or a service
Bulb change possible	technician commissioned by him or a similarly qualified person.
Rated life time L90/B10 at 25 °C	50.000 h
Energy efficiency class	nicht erforderlich

Mounting technology	
Mounting method	Surface mounting
Place of installation	Floor-mounted
Adjustability	Not adjustable
Material cover	Plastic, microprismatic

Packing data	
Gross weight	21.842 kg
Length of packaging	2,085 mm
Packaging width	520 mm
Packaging hight	95 mm
Disposal at end of life	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.

**Optional accessories** 

Article no.: 18209000 MELODY sensor user remote control

https://www.brumberg.com/fileadmin/products/Datenblatt\_18209000\_2021\_DE.pdf

All technical data as well as, weight and measurements are based on rated values and had been carefully prepared. We reserve the right to make technical changes which are are important in progressing. Product pictures are examples and can vary from the original. Subject to errors. Date 08.04.2025 Orders are placed under our general terms and conditions under https://www.brumberg.com/en/terms-and-conditions/general-terms-and-conditions-of-sale/