


APORIA LED-Pollerleuchte, IP54, Höhe 650 mm, schaltbar Article no. 65132103







Tende

Rectangular LED bollard luminaire, IP54, height 650 mm, switchable, luminaire length 168 mm, luminaire width 140 mm, height 650 mm, weight 2.980 kg, rated luminous flux 700 lm, rated wattage 1 x 14 W, light color warm white to warm white, most similar color temperature (CCT) 3.000 - 3,000 K, general color rendering index CRI > 80, housing material: aluminium / plastic, color: textured graphite, permissible ambient temperature (ta): -20 °C - +25 °C, protection class (EN 61140): I, degree of protection (DIN EN 60529): IP54. With electronic control gear, switchable.

Product Benefits

Bewegungsmelder:

Leuchtdauer: von 5 Sekunden bis 10 Minuten

Reichweite: 6 bis 10 Meter Erfassungswinkel: 120°

Einstellung bei Dämmerung: 20 - 2.000 Lux

Funktionsmodus: Ein / Aus, Leuchte wird nach Bewegung komplett ausgeschaltet



APORIA LED-Pollerleuchte, IP54, Höhe 650 mm, schaltbar Article no. 65132103

| Article data | |
|-------------------|---|
| Article no. | 65132103 |
| GTIN | 4251433982890 |
| Series name | APORIA |
| Short description | LED-Pollerleuchte, IP54, Höhe 650 mm, schaltbar |
| Material | Aluminium / Plastic |
| Colour | Graphite |
| Type of surface | Structure |
| Shape | Rectangular |
| Length | 168 mm |
| Width | 140 mm |
| Hight | 650 mm |
| Scope of delivery | inkl. Konverter zum Anschluss an 230 V-Netzspannung, schaltbar, mit Bewegungsmelder und |
| | Dämmerungsschalter |
| Weight | 2.980 kg |
| Conformance | CE, UKCA |

| Lighting technology | |
|------------------------------|---------------|
| Colour temperature | 3.000 K |
| Light colour | White |
| Light output | Direct |
| Luminous flux | 700 lm |
| System efficiency | 50 lm/W |
| McAdam-Step | McAdam-Step 6 |
| Colour rendering | CRI > 80 |
| Beam angle | 120° |
| Adjustable color temperature | No |

| Operating technology of the luminaire | |
|---------------------------------------|--|
| System output | 14 W |
| Voltage type | AC |
| AC nominal voltage max | 230 V |
| Frequency max | 50 Hz |
| Frequency min | 50 Hz |
| Lamp | LED |
| Lamp holder | Without fitting |
| Protection class | |
| Degree of protection | IP54 |
| Control | on/off |
| Bulb change possible | The light source of this luminaire may only be replaced by the manufacturer or a service |
| | technician commissioned by him or a similarly qualified person. |
| Energy efficiency class | nicht erforderlich |

| Mounting technology | |
|-----------------------|------------------|
| Mounting method | Surface mounting |
| Place of installation | Floor-mounted |
| Adjustability | Pivoted |
| Rotation angle | 60° |
| Further references | Outdoor |



APORIA LED-Pollerleuchte, IP54, Höhe 650 mm, schaltbar Article no. 65132103

| Packing data | |
|-------------------------|---|
| Gross weight | 3.94 kg |
| Length of packaging | 300 mm |
| Packaging width | 300 mm |
| Packaging hight | 800 mm |
| Disposal at end of life | This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment. |