


Article no. 12437074













LED recessed panel, TunableWhite, Round.Toolless ceiling installation by installation springs. Ceiling cut-out Ø 180 mm, Installation depth 30 mm, Outer diameter 200 mm, Weight 0,314 kg, with rotattionssymmetrical, deep, wide distributed light intensity. Cover plastic, opal. Power 1 x 20 W, Light colour warm white to daylight white, Correlated color temprature (CCT) 2.700 - 5.700 K, Colour rendering index CRI > 80, Housing material: Aluminium / Plastic, Colour: White, Permissible ambient temperature (ta): -20 °C - +25 °C, Protection class (EN 61140): III, Degree of protection (DIN EN 60529): IP20. For connection to an external driver, which is not included in the scope of delivery of the luminaire. Depending on driver dimmable.

Article data	
Article no.	12437074
GTIN	4251433915638
Series name	FLAT30
Short description	LED recessed panel, TunableWhite
Material	Aluminium / Plastic
Colour	White
Type of surface	Matt
Shape	Round
Outer diameter	200 mm
Built-in diameter	180 mm
Installation depth	30 mm
Hight	5 mm
Weight	0.314 kg
Conformance	CE, UKCA



Article no. 12437074

Lighting technology	
Colour temperature	2.700 K - 5.700 K
Light colour	White
Color Temperature 1	2,700 K
Color Temperature 2	5,700 K
Light output	Direct
Luminous flux 1	550 lm
Luminous flux 2	760 lm
System efficiency	20 lm/W
Colour rendering	CRI > 80
Reflector	Without
Beam angle	120°
Light sharing	Symmetric
Adjustable color temperature	Infinite control

Operating technology of the luminaire	
System output	20 W
Voltage type	DC
DC nominal voltage max	24 V
Lamp	LED
Protection class	
Degree of protection	IP20
Dimmable	Yes
Control	Depending on driver
Bulb change possible	The light source of this luminaire may only be replaced by the manufacturer or a service technician commissioned by him or a similarly qualified person.

Mounting technology	
Mounting method	Recessed mounting
Place of installation	Ceiling-mounted
Adjustability	Not adjustable
Max. ceiling thickness	13 mm
Further references	No cover with thermal insulation material
Material cover	Plastic, opal

Packing data	
Gross weight	0.486 kg
Length of packaging	250 mm
Packaging width	225 mm
Packaging hight	60 mm
Disposal at end of life	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that
	harmful substances get into the environment.



Article no. 12437074

Required accessories

Article no.: 17206000

LED power supply 24 V DC, 1-10 V dimmable (analog)

Power: 1 - 20 W

Dimensions: 145 mm x 55 mm x 19 mm

https://www.brumberg.com/fileadmin/products/Datenblatt_17206000_2021_DE.pdf

Article no.: 17207000

LED power supply 24 V DC, on/off switchable

Power: 1 - 30 W

Dimensions: 160 mm x 50 mm x 22 mm

https://www.brumberg.com/fileadmin/products/Datenblatt_17207000_2021_DE.pdf

Article no.: 17223000

LED power supply 24 V DC, on/off switchable

Power: 1 - 75 W

Dimensions: 185 mm x 60 mm x 31 mm

https://www.brumberg.com/fileadmin/products/Datenblatt_17223000_2021_DE.pdf

Article no.: 17224000

LED power supply 24 V DC, on/off switchable

Power: 1 - 100 W

Dimensions: 199 mm x 63 mm x 36 mm

https://www.brumberg.com/fileadmin/products/Datenblatt_17224000_2021_DE.pdf

Article no.: 17225000

LED power supply 24 V DC, on/off switchable

Power: 1 - 150 W

Dimensions: 219 mm x 63 mm x 36 mm

https://www.brumberg.com/fileadmin/products/Datenblatt 17225000 2021 DE.pdf

Article no.: 17226000

LED power supply 24V DC, on/off switchable

Power: 1 - 240 W

Dimensions: 244 mm x 71 mm x 38 mm

https://www.brumberg.com/fileadmin/products/Datenblatt_17226000_2021_DE.pdf

Article no.: 17240000

LED power supply 24 V DC, on/off switchable

Power: 1 - 20 W

Dimensions: 150 mm x 40 mm x 30 mm

https://www.brumberg.com/fileadmin/products/Datenblatt 17240000 2021 DE.pdf

Article no.: 17241000

LED power supply 24 V DC, on/off switchable

Power: 1 - 40 W

Dimensions: 210 mm x 40 mm x 30 mm

https://www.brumberg.com/fileadmin/products/Datenblatt 17241000 2021 DE.pdf

Article no.: 17242000

LED power supply 24 V DC, on/off switchable

Power: 1 - 60 W

Dimensions: 250 mm x 40 mm x 30 mm

https://www.brumberg.com/fileadmin/products/Datenblatt 17242000 2021 DE.pdf

Article no.: 17243000

LED power supply 24 V DC, on/off switchable

Power: 1 - 120 W

Dimensions: 300 mm x 40 mm x 30 mm

https://www.brumberg.com/fileadmin/products/Datenblatt_17243000_2021_DE.pdf



Article no. 12437074

Required accessories

Article no.: 17244000

LED power supply 24 V DC, on/off switchable

Power: 1 - 150 W

Dimensions: 310 mm x 40 mm x 30 mm

https://www.brumberg.com/fileadmin/products/Datenblatt_17244000_2021_DE.pdf

Article no.: 17230000

LED power supply 24 V DC, dimmable

Power: 5 - 30 W

Dimensions: 145 mm x 50 mm x 22 mm

https://www.brumberg.com/fileadmin/products/Datenblatt_17230000_2021_DE.pdf

Article no.: 17231000

LED power supply 24 V DC, dimmable

Power: 12 - 75 W

Dimensions: 185 mm x 60 mm x 31 mm

https://www.brumberg.com/fileadmin/products/Datenblatt_17231000_2021_DE.pdf

Article no.: 17232000

LED power supply 24 V DC, dimmable

Power: 12 - 120 W

Dimensions: 223 mm x 64 mm x 32 mm

https://www.brumberg.com/fileadmin/products/Datenblatt 17232000 2021 DE.pdf