



QUALITYFLEX ONE RGBW LED flex lighting 5 m, 14,4 W / m, IP67

Article no. 38274002

Light.
For Generations.



Tender

RGBW LED flex lighting 5 m, 14,4 W / m, IP67, rgbw, 3.000K, CRI > 90. LED flex lighting Length: 5000.0 mm Lamp power per meter: 14.4 W/m, Degree of protection: IP67, Protection class: III, Voltage: 24V DC, Beam angle: 120.0 °, 60 LEDs per meter, Chip distance (Short Pitch) : 16,7mm. For individual application, the LED flex board can be used all 200 mm be cut back. If the LED flex board is shortened, the IP protection must be restored by the customer. The maximum system length of 5.000mm must not be exceeded with one feed-in.

Product Benefits

- Dynamic color accents with red, green, blue and white.
- Suitable for indoor and outdoor use (IP67).
- Optimal for color accent lighting in residential or hospitality applications.
- Decorative lighting and accent lighting of cove lights, linear applications and backlights.
- Compatible with our 4-channel 24 V DC controllers, RGBW.

Article data	
Article no.	38274002
GTIN	4251433954231
Series name	QUALITYFLEX ONE
Short description	RGBW LED flex lighting 5 m, 14,4 W / m, IP67
Colour	RGBW
Length	5,000 mm
Width	15 mm
Height	5 mm
Scope of delivery	incl. 1 x mounting instructions, 5 x identification labels
Weight	0.545 kg
Length of the connection line	350 mm

QUALITYFLEX ONE RGBW LED flex lighting 5 m, 14,4 W / m, IP67

Article no. 38274002

Light.
For Generations.

Lighting technology	
Colour temperature	RGBW
Light colour	RGBW
Farbtemperatur 1	3,000 K
Lichtstrom 1	708 lm/m
Lichtstrom rot	86 lm/m
Lichtstrom grün	223 lm/m
Lichtstrom blau	48 lm/m
System efficiency	14 lm/W
Colour rendering	CRI > 90
Beam angle	120°
Adjustable color temperature	Infinite control

Operating technology of the luminaire	
Lamp power per meter	14.4 W/m
Voltage type	DC
DC nominal voltage max	24 V
Lamp	LED
Protection class	III
Degree of protection	IP67
Ambient temperature	-10 °C up to +40 °C
Dimmable	Yes
Wire number	5
Control	Depending on driver
Length of the connection line	350 mm
Kabelbelegung	white = + green = - green red = - red blue = - blue yellow = - white
Design of the connecting cable	both sides
Bulb change possible	No
Rated life time L70/B50 at 25 °C	168,000 h

Operating technology of QualityFlex	
Short Pitch	16.7 mm
Number of lamps per meter	60 Qty
Length of individual sections	200 mm
Smallest bend radius	60 mm
Length	5,000 mm
Maximum module length	5,000 mm
Circuit type	Parallel conduction
LED Type	5050 LED

Packing data	
Gross weight	0.555 kg
Length of packaging	250 mm
Packaging width	280 mm
Packaging height	20 mm
Disposal at end of life	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.

QUALITYFLEX ONE RGBW LED flex lighting 5 m, 14,4 W / m, IP67

Article no. 38274002

Light.
For Generations.

Compatible Driver						
Article no.	Power min	Power	Control	Length	Width	Hight
17206000	1 W	20 W	1-10 V	146 mm	55 mm	19 mm
17207000	1 W	30 W	on/off	160 mm	50 mm	22 mm
17214000	1 W	7.2 W	on/off	68 mm	35 mm	21 mm
17223000	1 W	75 W	on/off	185 mm	60 mm	31 mm
17224000	1 W	100 W	on/off	199 mm	63 mm	36 mm
17225000	1 W	150 W	on/off	219 mm	63 mm	36 mm
17226000	1 W	240 W	on/off	244 mm	71 mm	38 mm
17240000			on/off			

Compatible Controller						
Article no.	Power min	Power	Control	Length	Width	Hight
18151000	1 W	240 W	KNX	170 mm	59 mm	30 mm
18152000	1 W	240 W	DALI-DT6	170 mm	59 mm	30 mm
18153000	1 W	240 W	DMX	170 mm	59 mm	30 mm
18154000	1 W	240 W	1-10 V	170 mm	59 mm	30 mm
18161000	1 W	240 W	KNX	72 mm	90 mm	70 mm
18162000	1 W	240 W	DALI-DT6	54 mm	110 mm	66 mm
18164000	1 W	240 W	1-10 V	54 mm	110 mm	66 mm
18223000	0 W	240 W	Wireless technology control			
18157000	48 W	240 W	Zigbee	145 mm	46.5 mm	16 mm
18192000	120 W	240 W	Wireless technology control	160 mm	45 mm	18 mm

Compatible Profiles				
Short description	Series name	Length	Width	Hight
Surface-mounted profile	P06-20	2,000 mm	23 mm	25.1 mm
LED surface-mounted profile	P30-30	2,000 mm	33.4 mm	29.6 mm
Surface-mounted profile	P16-16	2,000 mm	18.8 mm	18.6 mm
Recessed profile	P36-20	2,000 mm	30 mm	20.4 mm
LED recessed profile	P40-30	2,000 mm	44.4 mm	24 mm
Plaster profile	P37-30	2,000 mm	63.4 mm	15.9 mm
Plaster profile	P38-30	2,000 mm	63.4 mm	24 mm
Flat profile P76-16	P76-16	2,000 mm	20.5 mm	3.8 mm
Surface-mounted cooling profile	ONE		20.5 mm	3.8 mm