


KEDIRI LED wall surface mounted luminaire, IP54

Article no. 65171103







Tender

LED wall surface mounted luminaire, IP54, Rectangular.Luminaire length 120.0 mm, Luminaire width 100.0 mm, Hight 380.0 mm Weight 2.713 kg., Luminous flux 750 lm, Power 1 x 11 W, Light colour warm white to warm white, Correlated color temprature (CCT) 3.000 - 3.000 K, Colour rendering index CRI > 80, Housing material: Aluminium / Plastic, Colour: Graphite structure, Permissible ambient temperature (ta): -20 °C - +25 °C, Protection class (EN 61140): I, Degree of protection (DIN EN 60529): IP54. With electronic driver, on/off switchable.

| Article data | |
|-------------------|---|
| Article no. | 65171103 |
| GTIN | 4251433982876 |
| Series name | KEDIRI |
| Short description | LED wall surface mounted luminaire, IP54 |
| Material | Aluminium / Plastic |
| Colour | Graphite |
| Type of surface | Structure |
| Shape | Rectangular |
| Length | 120 mm |
| Width | 100 mm |
| Hight | 380 mm |
| Scope of delivery | incl. converter for connection to 230 V mains voltage, switchable |
| Weight | 2.713 kg |
| Conformance | CE, UKCA |



KEDIRI LED wall surface mounted luminaire, IP54

Article no. 65171103

| Lighting technology | |
|------------------------------|---------------|
| Colour temperature | 3.000 K |
| Light colour | White |
| Light output | Direct |
| Luminous flux | 750 lm |
| System efficiency | 68 lm/W |
| McAdam-Step | McAdam-Step 6 |
| Colour rendering | CRI > 80 |
| Beam angle | 110° |
| Adjustable color temperature | No |

| Operating technology of the luminaire | |
|---------------------------------------|--|
| System output | 11 W |
| Voltage type | AC |
| AC nominal voltage max | 230 V |
| Frequency max | 50 Hz |
| Frequency min | 50 Hz |
| Lamp | LED |
| Lamp holder | Without fitting |
| Protection class | |
| Degree of protection | IP54 |
| Control | on/off |
| Bulb change possible | The light source of this luminaire may only be replaced by the manufacturer or a service |
| | technician commissioned by him or a similarly qualified person. |

| Mounting technology | |
|-----------------------------|------------------|
| Mounting method | Surface mounting |
| Place of installation | Wall-mounted |
| Adjustability | Not adjustable |
| Further references | Outdoor |
| Suitable for through-wiring | No |

| Packing data | |
|-------------------------|---|
| Gross weight | 3.673 kg |
| Length of packaging | 300 mm |
| Packaging width | 300 mm |
| Packaging hight | 800 mm |
| | This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. |
| Disposal at end of life | By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that |
| | harmful substances get into the environment. |