




**QUALITYFLEX Performance LED flex lighting, 5 m, CRI > 95, 15 W / m, IP00**  
Article no. 19304027

Light.  
For Generations.



#### Tender

LED flex lighting, 5 m, CRI > 95, 15 W / m, IP00, white, 2.700K, CRI > 95. LED flex lighting Length: 5000.0 mm Lamp power per meter: 15.0 W/m, Luminous flux per meter: 1170.0 lm/m, Degree of protection: IP00, Protection class: III, Voltage: 24V DC, Beam angle: 120.0 °, 60 LEDs per meter, Chip distance (Short Pitch) : 16,7mm. For individual application, the LED flex board can be used all 100 mm be cut back. The maximum system length of 10.000mm must not be exceeded with one feed-in.

#### Product Benefits

- Very high color rendering with CRI>95.
- Length of maximum 10 meters can be realized with one feed-in.
- Suitable for indoor dry areas (IP00).
- Pitch of 100 millimeters.
- High light output for indirect and ambient lighting in numerous applications.
- Available in 2700 Kelvin, 3000 Kelvin and 4000 Kelvin.
- Dimmable with appropriate accessories.

**QUALITYFLEX Performance LED flex lighting, 5 m, CRI > 95, 15 W / m, IP00**

Article no. 19304027

Light.  
For Generations.

| Article data                  |  |
|-------------------------------|--|
| Article no.                   | 19304027   |
| GTIN                          | 4251433927662  |
| Series name                   | QUALITYFLEX Performance                                    |
| Short description             | LED flex lighting, 5 m, CRI > 95, 15 W / m, IP00           |
| Colour                        | White  |
| Length                        | 5,000 mm   |
| Width                         | 10 mm  |
| Height                        | 1.4 mm   |
| Scope of delivery             | incl. 1 x mounting instructions, 5 x identification labels |
| Weight                        | 0.122 kg   |
| Length of the connection line | 350 mm   |
| Conformance                   | CE, UKCA   |

| Lighting technology          |               |
|------------------------------|---------------|
| Colour temperature           | 2.700 K       |
| Light colour                 | White         |
| Luminous flux per meter      | 1,170 lm/m    |
| System efficiency            | 78 lm/W       |
| McAdam-Step                  | McAdam-Step 5 |
| Colour rendering             | CRI > 95      |
| Beam angle                   | 120°          |
| Adjustable color temperature | No            |

| Operating technology of the luminaire |                                |
|---------------------------------------|--------------------------------|
| System output                         | 75 W                           |
| Lamp power per meter                  | 15 W/m                         |
| Voltage type                          | DC                             |
| DC nominal voltage max                | 24 V                           |
| Lamp                                  | LED                            |
| Protection class                      | III                            |
| Degree of protection                  | IP00                           |
| Ambient temperature                   | -10 °C up to +40 °C            |
| Dimmable                              | Yes                            |
| Wire number                           | 2                              |
| Control                               | Depending on driver            |
| Length of the connection line         | 350 mm                         |
| Cable assignment                      | rot = + pol<br>schwarz = - pol |
| Design of the connecting cable        | both sides                     |
| Bulb change possible                  | No                             |
| Rated life time L70/B50 at 25 °C      | 50,000 h                       |
| Rated life time L80/B10 at 25 °C      | 50.000 h                       |
| Energy efficiency class               | F                              |

| Operating technology of QualityFlex |                     |
|-------------------------------------|---------------------|
| Power per meter                     | 15 W/m              |
| Short Pitch                         | 16.7 mm             |
| Number of lamps per meter           | 60 Qty              |
| Length of individual sections       | 100 mm              |
| Smallest bend radius                | 40 mm               |
| Length                              | 5,000 mm            |
| Maximum module length               | 10,000 mm           |
| Circuit type                        | Parallel conduction |
| LED Type                            | 2835 LED            |

**QUALITYFLEX Performance LED flex lighting, 5 m, CRI > 95, 15 W / m, IP00**  
Article no. 19304027

Light.  
For Generations.

| Packing data            |  |
|-------------------------|--|
| Gross weight            | 0.156 kg   |
| Length of packaging     | 220 mm   |
| Packaging width         | 240 mm   |
| Packaging height        | 20 mm  |
| Disposal at end of life | <p>This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately.</p> <p>By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.</p> |

| Compatible Driver |           |       |                     |        |       |       |
|-------------------|-----------|-------|---------------------|--------|-------|-------|
| Article no.       | Power min | Power | Control             | Length | Width | Hight |
| 17206000          | 1 W       | 20 W  | 1-10 V              | 146 mm | 55 mm | 19 mm |
| 17207000          | 1 W       | 30 W  | on/off              | 160 mm | 50 mm | 22 mm |
| 17214000          | 1 W       | 7.2 W | on/off              | 68 mm  | 35 mm | 21 mm |
| 17223000          | 1 W       | 75 W  | on/off              | 185 mm | 60 mm | 31 mm |
| 17224000          | 1 W       | 100 W | on/off              | 199 mm | 63 mm | 36 mm |
| 17225000          | 1 W       | 150 W | on/off              | 219 mm | 63 mm | 36 mm |
| 17226000          | 1 W       | 240 W | on/off              | 244 mm | 71 mm | 38 mm |
| 17230000          |           |       | Trailing-edge phase |        |       |       |
| 17240000          |           |       | on/off              |        |       |       |

| Compatible Controller |           |       |                             |        |         |       |
|-----------------------|-----------|-------|-----------------------------|--------|---------|-------|
| Article no.           | Power min | Power | Control                     | Length | Width   | Hight |
| 18151000              | 1 W       | 240 W | KNX                         | 170 mm | 59 mm   | 30 mm |
| 18152000              | 1 W       | 240 W | DALI-DT6                    | 170 mm | 59 mm   | 30 mm |
| 18153000              | 1 W       | 240 W | DMX                         | 170 mm | 59 mm   | 30 mm |
| 18154000              | 1 W       | 240 W | 1-10 V                      | 170 mm | 59 mm   | 30 mm |
| 18161000              | 1 W       | 240 W | KNX                         | 72 mm  | 90 mm   | 70 mm |
| 18162000              | 1 W       | 240 W | DALI-DT6                    | 54 mm  | 110 mm  | 66 mm |
| 18164000              | 1 W       | 240 W | 1-10 V                      | 54 mm  | 110 mm  | 66 mm |
| 17528000              | 1 W       | 240 W | Wireless technology control |        |         |       |
| 17502000              | 1 W       | 120 W | DALI                        | 183 mm | 33 mm   | 23 mm |
| 18157000              | 1 W       | 240 W | ZigBee                      | 145 mm | 46.5 mm | 16 mm |
| 18192000              | 1 W       | 240 W | Wireless technology control | 160 mm | 45 mm   | 18 mm |
| 18207000              |           |       |                             | 137 mm | 45 mm   | 13 mm |
| 18199000              |           |       |                             |        |         |       |
| 18202000              |           |       |                             |        |         |       |

**QUALITYFLEX Performance LED flex lighting, 5 m, CRI > 95, 15 W / m, IP00**

Article no. 19304027

Light.  
For Generations.

| Compatible Profiles                        |             |          |         |         |
|--|-------------|----------|---------|---------|
| Short description                          | Series name | Length   | Width   | Hight   |
| Recessed profile<br>53654070               | P36-20      | 2,000 mm | 30 mm   | 20.4 mm |
| LED recessed profile<br>53759070           | P40-30      | 2,000 mm | 44.4 mm | 24 mm   |
| Wall recessed profile<br>53650260          | P32-12      | 2,000 mm | 19.1 mm | 81 mm   |
| Plaster profile<br>53655070                | P37-30      | 2,000 mm | 63.4 mm | 15.9 mm |
| Plaster profile<br>53656070                | P38-30      | 2,000 mm | 63.4 mm | 24 mm   |
| Surface-mounted profile<br>53600070        | P01-10      | 2,000 mm | 20 mm   | 8 mm    |
| Surface-mounted profile<br>53602070        | P04-14      | 2,000 mm | 24 mm   | 9 mm    |
| Surface-mounted profile<br>53603070        | P06-20      | 2,000 mm | 23 mm   | 25.1 mm |
| LED surface-mounted profile<br>53606070    | P30-30      | 2,000 mm | 33.4 mm | 29.6 mm |
| Surface-mounted profile<br>53607080        | P16-16      | 2,000 mm | 18.8 mm | 18.6 mm |
| Surface-mounted profile, flat<br>53380261  | ONE         |          | 17.6 mm | 6 mm    |
| Surface-mounted profile, high<br>53381302  | ONE         |          | 17.6 mm | 15.9 mm |
| Surface-mounted corner profile<br>53700070 | P60-10      | 2,000 mm | 20 mm   | 16 mm   |
| Surface-mounted corner profile<br>53702070 | P62-14      | 2,000 mm | 24 mm   | 19.4 mm |
| Surface-mounted corner profile<br>53703260 | P63-14      | 2,000 mm | 17.5 mm | 17.5 mm |
| Surface-mounted corner profile<br>53385261 | ONE         |          | 24 mm   | 19.4 mm |
| Flexible profile<br>53753260               | P72-12      | 2,000 mm | 20 mm   | 3.3 mm  |
| Wall surface-mounted profile<br>53754070   | P73-12      | 2,000 mm | 17.8 mm | 46.1 mm |
| Wall surface-mounted profile<br>53751260   | P74-14      | 2,000 mm | 18.5 mm | 55 mm   |
| Flat profile P76-16<br>53756070            | P76-16      | 2,000 mm | 20.5 mm | 3.8 mm  |
| Surface-mounted round profile<br>53760260  | P90-16      | 2,000 mm | 20 mm   | 17 mm   |