
## **BRUMBERG**


### ARTEMIS MIDI LED recessed spotlight, DALI

Article no. 88263164DA

Light. For Generations.









#### Tende

LED recessed spotlight, DALI, Round. Ceiling cut-out Ø 152 mm, Installation depth 128 mm, Outer diameter 164 mm, with rotationssymmetrical, deep, wide distributed light intensity. optimal light distribution due to a glass transparent cover.Luminous flux 3.962 lm, Power 1 x 31,5 W, Light colour neutral white, Correlated color temprature (CCT) 4.000 K, Colour rendering index CRI > 90, Housing material: Aluminium, Colour: Silver structure, Permissible ambient temperature (ta): -20 °C - +25 °C, Protection class (EN 61140): II, Degree of protection (DIN EN 60529): IP20, .With electronic driver, DALI dimmable.

| Article data       |                              |
|--------------------|------------------------------|
| Article no.        | 88263164DA                   |
| GTIN               | 4251433984696                |
| Series name        | ARTEMIS MIDI                 |
| Short description  | LED recessed spotlight, DALI |
| Material           | Aluminium                    |
| Colour             | Silver                       |
| Type of surface    | Structure                    |
| Shape              | Round                        |
| Outer diameter     | 164 mm                       |
| Built-in diameter  | 152 mm                       |
| Installation depth | 128 mm                       |
| Weight             | N.N.                         |

# **BRUMBERG**

## ARTEMIS MIDI LED recessed spotlight, DALI

Article no. 88263164DA

Light. For Generations.

| Lighting technology |            |
|---------------------|------------|
| Colour temperature  | 4.000 K    |
| Light colour        | White      |
| Light output        | Direct     |
| Luminous flux       | 3,962 lm   |
| System efficiency   | 126 lm/W   |
| Colour rendering    | CRI > 90   |
| Reflector           | High-gloss |
| Beam angle          | 30°        |
| Light sharing       | Symmetric  |

| Operating technology of the luminaire |  |
|---------------------------------------|--|
| Voltage type                          | AC   |
| AC nominal voltage max                | 230 V  |
| Frequenz max.                         | 50 Hz  |
| Lamp                                  | LED  |
| Protection class                      |  |
| Degree of protection                  | IP20   |
| Control                               | DALI   |
| Bulb change possible                  | The light source of this luminaire may only be replaced by the manufacturer or a service technician commissioned by him or a similarly qualified person. |

| Mounting technology         |   |
|-----------------------------|---|
| Mounting method             | Recessed mounting                         |
| Place of installation       | Ceiling-mounted                           |
| Adjustability               | Rotatable and adjustable head             |
| Swivel angle                | 90°                                       |
| Rotation angle              | 350°                                      |
| Head adjustable angle       | 90°                                       |
| Further references          | No cover with thermal insulation material |
| Material cover              | Glass transparent                         |
| Suitable for through-wiring | No  |

| Packing data            |  |
|-------------------------|--|
| Gross weight            | N.N.   |
| Length of packaging     | N.N.   |
| Packaging width         | N.N.   |
| Packaging hight         | N.N.   |
| Disposal at end of life | This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately.  By disposing of electrical waste and other old or defective electronics separately, you |
|                         | support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.   |