




CUBA LED-Einbaustrahler set, dreh- und schwenkbar, schaltbar

Article no. 12310183


Tender

Round LED recessed spotlight set, rotatable and tiltable, switchable, tool-free ceiling installation using installation springs. Ceiling cut-out Ø 60 mm, installation depth 40 mm, weight 0.306 kg, silver reflector with rotationally symmetrical deep-wide beam light distribution. Rated luminous flux 250 lm, rated wattage 1 x 4.2 W, light color warm white, most similar color temperature (CCT) 3,000 K, general color rendering index CRI > 90, housing material: aluminum / plastic, color: textured black, permissible ambient temperature (ta): -20 °C - +25 °C, protection class (EN 61140): I, degree of protection (DIN EN 60529): IP20. With electronic control gear, switchable.

Product Benefits

- LED-Einbaustrahler in runder Bauform aus Aluminium.
- Leuchtenkopf dreh- (355°) und schwenkbar (25°).
- Deckenausschnitt 60 mm, Außendurchmesser 68 mm (Abdeckplatte Deckenausschnitt), Einbautiefe 40 mm, Lichtstrom 250 lm, IP20.
- Set inklusive Konverter schaltbar.

CUBA LED-Einbaustrahler, dreh- und schwenkbar, schaltbar

Article no. 12310183

Article data	
Article no.	12310183
GTIN	4251433932444
Series name	CUBA
Short description	LED-Einbaustrahler, dreh- und schwenkbar, schaltbar
Material	Aluminium / Plastic
Colour	Black
Type of surface	Structure
Shape	Round
Built-in diameter	60 mm
Installation depth	40 mm
Hight	125 mm
Weight	0.306 kg
Conformance	CE, UKCA

Lighting technology	
Colour temperature	3.000 K
Light output	Direct
Luminous flux	250 lm
System efficiency	60 lm/W
Colour rendering	CRI > 90
Reflector	High-gloss
Reflector colour	silver
Beam angle	38°
Light sharing	Symmetric
Adjustable color temperature	No

Operating technology of the luminaire	
System output	4.2 W
Voltage type	AC
AC nominal voltage max	230 V
Current	350 mA
Frequency max	50 Hz
Lamp	LED
Lamp holder	Without fitting
Protection class	I
Degree of protection	IP20
Dimmable	No
Control	on/off
Bulb change possible	The light source of this luminaire may only be replaced by the manufacturer or a service technician commissioned by him or a similarly qualified person.
Energy efficiency class	nicht erforderlich

Mounting technology	
Mounting method	Recessed mounting
Place of installation	Ceiling-mounted
Adjustability	Rotatable and adjustable head
Swivel angle	25°
Rotation angle	355°
Head adjustable angle	25°
Max. ceiling thickness	28 mm
Further references	No cover with thermal insulation material
Pendulum length min.	30 mm
Material cover	Without cover
Suitable for through-wiring	Yes, with optional accessories

CUBA LED-Einbaustrahlerset, dreh- und schwenkbar, schaltbar

Article no. 12310183

Packing data	
Gross weight	0.474 kg
Length of packaging	225 mm
Packaging width	135 mm
Packaging height	100 mm
Disposal at end of life	<p>This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately.</p> <p>By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.</p>

Optional accessories	
Article no.: 83330000	
Connection box 230 V AC, 3-pole	
Dimensions: 80 mm x 41 mm x 34 mm	
https://www.brumberg.com/fileadmin/products/Datenblatt_83330000_2021_DE.pdf	