



BLOKK LED ceiling surface-mounted luminaire, IP65

Article no. 60116103



Tender

LED ceiling surface-mounted luminaire, IP65, Square. Luminaire length 110.0 mm, Luminaire width 110.0 mm, Height 100.0 mm Weight 1.437 kg, Cover glass transparent. Luminous flux 1.600 lm, Power 21 W, Light colour warm white, Correlated color temprature (CCT) 3.000 K, Colour rendering index CRI > 80, Housing material: Aluminium / Glass, Colour: Graphite structure, Permissible ambient temperature (ta): -20 to +45°C, Protection class (EN 61140): I, Degree of protection (DIN EN 60529): IP65. For connection to an external driver, which is not included in the scope of delivery of the luminaire. on/off switchable.

Article data	
Article no.	60116103
GTIN	4251433925736
Series name	BLOKK
Short description	LED ceiling surface-mounted luminaire, IP65
Material	Aluminium / Glass
Colour	Graphite
Type of surface	Structure
Shape	Square
Length	110 mm
Width	110 mm
Hight	100 mm
Scope of delivery	Incl. converter for connection to the 230-V mains voltage
Weight	1.437 kg
Conformance	CE, UKCA

BLOKK LED ceiling surface-mounted luminaire, IP65

Article no. 60116103

Lighting technology	
Colour temperature	3.000 K
Light colour	White
Luminous flux	1,600 lm
System efficiency	76 lm/W
McAdam-Step	McAdam-Step 3
Colour rendering	CRI > 80
Beam angle	32°
Adjustable color temperature	No

Operating technology of the luminaire	
System output	21 W
Voltage type	AC
AC nominal voltage max	230 V
Frequency max	50 Hz
Frequency min	50 Hz
Lamp	LED
Lamp holder	Without fitting
Protection class	I
Degree of protection	IP65
Ambient temperature	-20 to +45°C
Dimmable	No
Control	on/off
Bulb change possible	The light source of this luminaire may only be replaced by the manufacturer or a service technician commissioned by him or a similarly qualified person.

Mounting technology	
Mounting method	Surface mounting
Place of installation	Ceiling-mounted
Adjustability	Not adjustable
Further references	Outdoor
Material cover	Glass transparent
Suitable for through-wiring	Yes

Packing data	
Gross weight	1.521 kg
Length of packaging	130 mm
Packaging width	120 mm
Packaging height	120 mm
Disposal at end of life	<p>This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately.</p> <p>By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.</p>