



IMPLEMENT LED surface mounted downlight, trailing-edge phase dimmable

Article no. 12394173

Light.
For Generations.**Tender**

LED surface mounted downlight, trailing-edge phase dimmable, white structure, Round. Surface mounting, Ceiling-mounted Luminaire incl. converter for 230 V mains voltage, trailing-edge phase dimmable. Mounting method: Surface mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) I, Voltage: 230V AC 50Hz, Power: 8.9 W, Amount of light sources / fittings: 1 Qty, Luminous flux : 730 lm, Colour temperature: 3.000 K, Beam angle: 37°, Adjustability: Not adjustable, With control gear: Yes, Dimmable: Yes, Control: Trailing-edge phase.

Product Benefits

- Ceiling surface-mounted luminaire made of massive aluminium.
- Diameter 94 mm, installation height 114 mm.
- Luminous flux 730 lm, IP20.
- Continuously dimmable.
- 5 different products are available in optically identical interior optics.
- This allows the realization of the projects with different mounting types recessed and surface mounting in different outer shells with similar internal insert.

IMPLEMENT LED surface mounted downlight, trailing-edge phase dimmable

Article no. 12394173

Light.
For Generations.

Article data	
Article no.	12394173
GTIN	4251433933045
Series name	IMPLEMENT
Short description	LED surface mounted downlight, trailing-edge phase dimmable
Material	Aluminium / Plastic
Colour	White
Type of surface	Structure
Shape	Round
Outer diameter	94 mm
Hight	114 mm
Scope of delivery	incl. converter for connection to 230 V mains voltage, trailing-edge phase dimmer
Weight	0.748 kg

Lighting technology	
Colour temperature	3.000 K
Light colour	White
Light output	Direct
Luminous flux	730 lm/m
System efficiency	82 lm/W
Colour rendering	CRI > 90
Reflector	High-gloss
Reflektorfarbe	silver
Beam angle	37°
Light sharing	Symmetric

Operating technology of the luminaire	
System output	8.9 W
Voltage type	AC
AC nominal voltage max	230 V
Frequenz max.	50 Hz
Lamp	LED
Protection class	I
Degree of protection	IP20
Dimmable	Yes
Control	Trailing-edge phase
Bulb change possible	Yes

Mounting technology	
Mounting method	Surface mounting
Place of installation	Ceiling-mounted
Adjustability	Not adjustable
Material cover	Plastic, transparent

Packing data	
Gross weight	0.855 kg
Length of packaging	135 mm
Packaging width	135 mm
Packaging hight	140 mm
Disposal at end of life	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.