

CC2050

TYPE 2–TYPE 2 CHARGING CABLE

Up to 11 kW

The CC2050 is a mode 3 charging cable for connecting an electric vehicle with a type 2 charging connector to a charging station with a type 2 charging socket. The charging cable, which weighs just 1.9 kg, has a length of 5 metres and is designed for a maximum charging power of 11 kW with a charging current of up to 20 A and a rated voltage of 480 V. With over 10,000 mating cycles, the CC2050 is particularly durable and reliable in operation.



General information

Model	Type 2 to Type 2 charging cable
Product number	CC2050
EAN number	4011721190198
Commodity code	85444290
Packaging unit (PU)	1 unit
Packaging (dimensions HxWxD)	9 × 51 × 35.5 cm
Net weight	1.9 kg
Gross weight	2.4 kg
Items supplied	Mode 3 charging cable, operating instructions

Charging cable specifications

Cable length	5 m
Number of phases	3
Maximum output	11 kW
Rated current (power)	20 A
Rated voltage (power)	480 V
Mating cycles	≥ 10,000
IP rating	IP44 (when plugged in)
Operating temperature	-30 to 50°C
Ambient temperature (storage)	-40 to 80°C
Colour	Black
Standards	IEC 62196-2

Subject to change: All performance characteristics, technical and other specifications are subject to change without prior notice.

Revision status ABL_CC2050_EN_a, 03/22

1

ABL GmbH · Albert-Büttner-Straße 11 · D-91207 Lauf / Pegnitz · Phone +49 (0) 9123 188-0 · Fax +49 (0) 9123 188-188 · info@abl.de · www.abl.de · www.ablmobility.de