


KACIE MINI LED Surface-mounted downlight, DALI dimmable

Article no. 12595184DA

Light.
For Generations.**Tender**

LED Surface-mounted downlight, DALI dimmable, Round. Luminaire diameter 190.0 mm, Height 150.0 mm Weight 1.751 kg, Reflector silver with rotationssymmetrical, deep, wide distributed light intensity.. Luminous flux 3.541 lm, UGR < 20, Power 1 x 31 W, Light colour neutral white, Correlated color temprature (CCT) 4.000 K, Colour rendering index CRI > 90, Rated life time L70/B10 at 25 °C: 50.000 h, Rated life time L70/B50 at 25 °C: 50.000 h, Housing material: Aluminium / Plastic, Colour: Black structure, Permissible ambient temperature (ta): -20 °C - +25 °C, Protection class (EN 61140): I, Degree of protection (DIN EN 60529): IP20. With electronic driver, DALI-2 dimmable.

Product Benefits

- Round surface-mounted downlight made of solid aluminum with generously dimensioned heat management.
- High-quality reflector.
- Simple installation.
- CRI > 90, UGR < 20.
- Available in switchable and DALI dimmable versions.

KACIE MINI LED Surface-mounted downlight, DALI dimmable

Article no. 12595184DA

Light.
For Generations.

Article data	
Article no.	12595184DA
GTIN	4251433999706
Series name	KACIE MINI
Short description	LED Surface-mounted downlight, DALI dimmable
Material	Aluminium / Plastic
Colour	Black
Type of surface	Structure
Shape	Round
Outer diameter	190 mm
Height	150 mm
Scope of delivery	incl. converter for connection to 230 V mains voltage, DALI-2 dimmable
Weight	1.751 kg
Conformance	CE, UKCA

Lighting technology	
Colour temperature	4.000 K
Light colour	White
Light output	Direct
Luminous flux	3,541 lm
System efficiency	114 lm/W
Colour rendering	CRI > 90
Reflector	Faceted
Reflector colour	silver
Beam angle	70°
Glare evaluation	UGR < 20
Light sharing	Symmetric
Adjustable color temperature	No

Operating technology of the luminaire	
System output	31 W
Voltage type	AC
AC nominal voltage max	230 V
Frequency max	50 Hz
Lamp	LED
Protection class	I
Degree of protection	IP20
Dimmable	Yes
Control	DALI-2
Bulb change possible	The light source of this luminaire may only be replaced by the manufacturer or a service technician commissioned by him or a similarly qualified person.
Rated life time L70/B50 at 25 °C	50,000 h

Mounting technology	
Mounting method	Surface mounting
Place of installation	Ceiling-mounted
Adjustability	Not adjustable
Material cover	Without cover

KACIE MINI LED Surface-mounted downlight, DALI dimmable
Article no. 12595184DA

Light.
For Generations.

Packing data	
Gross weight	1.938 kg
Length of packaging	195 mm
Packaging width	190 mm
Packaging hight	215 mm
Disposal at end of life	<p>This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately.</p> <p>By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.</p>