



Article no. 32064074









Tende

right-angled LED recessed panel 1,245 x 308 mm, microprismatic cover, UGR<19, TunableWhite, DALI-2 DT-8 dimmable, recessed luminaire for ceilings with visible trunking. Ceiling cut-out L x W 1227 x 290 mm installation depth 40 mm, length 1,245 mm, width 308 mm, weight 3.000 kg, with rotationally symmetrical deep-wide beam light distribution. Plastic microprismatic cover, rated luminous flux 4,700 lm, UGR < 19, rated wattage 1 x 33 W, light color warm white to daylight white, most similar color temperature (CCT) 2,700 - 6,500 K, general color rendering index CRI > 80, service life L70/B10 at 25 °C: 110.000 h, service life L70/B50 at 25 °C: 125,000 h, service life L80/B10 at 25 °C: 78,000 h, service life L80/B50 at 25 °C: 100,000 h, housing material: aluminum / PMMA, color: white, permissible ambient temperature (ta): -20 °C to +45 °C, protection class (EN 61140): II, degree of protection (DIN EN 60529): IP20, degree of impact resistance according to IEC62262: IK04. With electronic control gear, DALI-2, PUSH-Dimm, DALI-DT8 dimmable. The luminaire is also ENEC-certified by an independent testing body.



Article no. 32064074

Article data	
Article no.	32064074
GTIN	4251433998389
Series name	OREN
Short description	LED panel 1245 x 308 mm TunableWhite MP DALI-2 DT-8
Material	Aluminium / PMMA
Colour	White
Shape	Rectangular
Length	1,245 mm
Width	308 mm
Built-in length	1227 mm
Built-in width	290 mm
Installation depth	40 mm
Hight	11 mm
Scope of delivery	incl. multilumen DALI-2 DT-8 driver.
	500 mA; 700 mA; 900 mA; 1.050 mA
Weight	3.000 kg
stamp	ENEC
Conformance	CE, UKCA

Lighting technology	
Colour temperature	2.700 K - 6.500 K
Light colour	White
Color Temperature 1	2,700 K
Color Temperature 2	6,500 K
Light output	Direct
Luminous flux	4,700 lm
Luminous flux 1	2,350 lm
Luminous flux 2	2,350 lm
System efficiency	124 lm/W
McAdam-Step	McAdam-Step 3
Colour rendering	CRI > 80
Reflector	Without
Beam angle	85°
Glare evaluation	UGR < 19
Light sharing	Symmetric
Photobio. Risk group according to EN 62778	RG0
Adjustable color temperature	Infinite control



Article no. 32064074

Operating technology of the luminaire	
System output	38 W
Voltage type	AC/DC
AC nominal voltage min	198 V
AC nominal voltage max	264 V
Frequency max	60 Hz
Frequency min	50 Hz
Lamp	LED
Lamp holder	Without fitting
Protection class	
Degree of protection	IP20
Ambient temperature	-20°C to +45°C
Dimmable	Yes
Control	DALI-2 , PUSH-Dimm, DALI-DT8
Pulh change possible	The light source of this luminaire may only be replaced by the manufacturer or a service
Bulb change possible	technician commissioned by him or a similarly qualified person.
Glow wire test according to IEC 60695-2-12	650°C
Rated life time L70/B50 at 25 °C	125,000 h
Rated life time L80/B10 at 25 °C	78.000 h
Rated life time L80/B50 at 25 °C	100.000 h
Rated life time L90/B10 at 25 °C	30.000 h
Energy efficiency class	nicht erforderlich
max. no. lights on B10 A	33
max. no. lights on B16 A	53
max. no. lights on C10 A	33
max. no. lights on C16 A	53

Operating technology of the luminaire	
Hight	11 mm
Lamp holder	Without fitting
Power	38 W
Voltage type	DC
Current	1.050 mA
Lamp	LED
Protection class	
Degree of protection	IP40
Rated life time L70/B50 at 25 °C	100,000 h
Bulb change possible	The light source of this luminaire may only be replaced by the manufacturer or a service technician commissioned by him or a similarly qualified person.

Mounting technology	
Mounting method	Recessed mounting
Place of installation	Ceiling-mounted
Adjustability	Not adjustable
Impact resistance	IK04
Further references	No cover with thermal insulation material
Material cover	Plastic, microprismatic
Suitable for through-wiring	Yes



Article no. 32064074

Packing data	
Gross weight	3.5 kg
Length of packaging	1,270 mm
Packaging width	360 mm
Packaging hight	35 mm
Disposal at end of life	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately.
	By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that
	harmful substances get into the environment.

Optional accessories

Article no.: 81032063

Installation frame 1-piece, 1,303 x 366 x 30 mm, white

Dimensions: 1,300 mm x 365 mm x 30 mm

https://www.brumberg.com/fileadmin/products/Datenblatt_81032063_2021_DE.pdf

Article no.: 81032064

Mounting frame 4-piece, 1,265 x 328 x 50 mm, white

Dimensions: 1,265 mm x 325 mm x 50 mm

https://www.brumberg.com/fileadmin/products/Datenblatt_81032064_2021_DE.pdf

Article no.: 81032069

Y-rope suspension set of 1 300/308mm

Dimensions: 2,000 mm

https://www.brumberg.com/fileadmin/products/Datenblatt_81032069_2021_DE.pdf

Article no.: 00532900

Installation spring set of 4 for LED panel

https://www.brumberg.com/fileadmin/products/Datenblatt_00532900_2021_DE.pdf