




**BB36 LED recessed spotlight set, switchable, with connection box**

Article no. 38497173


**Tender**

LED recessed spotlight set, switchable, with connection box, Square. Toolless ceiling installation by installation springs. Ceiling cut-out  $\varnothing$  68 mm, Installation depth 43 mm, Length 82 mm, Width 82 mm, Weight 0,246 kg, Reflector silver with rotationssymmetrical, deep, wide distributed light intensity. Cover polycarbonat clear. Luminous flux 680 lm, Power 1 x 7 W, Light colour warm white, Correlated color temperature (CCT) 3.000 K, Colour rendering index CRI > 80, Rated life time L70/B50 at 25 °C: 50.000 h, Housing material: Aluminium / Plastic, Colour: White structure, Permissible ambient temperature (ta): -20 °C - +25 °C, Protection class (EN 61140): II, Degree of protection (DIN EN 60529): IP20. With electronic driver, on/off switchable.

**BB36 LED recessed spotlight set, switchable, with connection box**

Article no. 38497173

| Article data       |   |
|--------------------|---|
| Article no.        | 38497173  |
| GTIN               | 4251433997290   |
| Series name        | BB36  |
| Short description  | LED recessed spotlight set, switchable, with connection box |
| Material           | Aluminium / Plastic   |
| Colour             | White   |
| Type of surface    | Structure   |
| Shape              | Square  |
| Built-in diameter  | 68 mm   |
| Installation depth | 43 mm   |
| Length             | 82 mm   |
| Width              | 82 mm   |
| Hight              | 4.5 mm  |
| Scope of delivery  | incl. connection box, 3-pole                                |
| Weight             | 0.246 kg  |
| Conformance        | CE, UKCA  |

| Lighting technology          |           |
|------------------------------|-----------|
| Colour temperature           | 3.000 K   |
| Light colour                 | White     |
| Light output                 | Direct    |
| Luminous flux                | 680 lm    |
| System efficiency            | 97 lm/W   |
| Colour rendering             | CRI > 80  |
| Reflector                    | Faceted   |
| Reflector colour             | silver    |
| Beam angle                   | 40°       |
| Light sharing                | Symmetric |
| Adjustable color temperature | No        |

| Operating technology of the luminaire |          |
|---------------------------------------|----------|
| Power                                 | 6 W      |
| Voltage type                          | DC       |
| Current                               | 350 mA   |
| Lamp                                  | LED      |
| Protection class                      | III      |
| Degree of protection                  | IP20     |
| Rated life time L70/B50 at 25 °C      | 30,000 h |

| Operating technology of driver |             |
|--------------------------------|-------------|
| Article No. of used driver     | 17662010    |
| Length                         | 68 mm       |
| Width                          | 35 mm       |
| Hight                          | 21 mm       |
| AC nominal voltage min         | 90 V        |
| AC nominal voltage max         | 264 V       |
| Frequency max                  | 60 Hz       |
| Dimmable                       | No          |
| Control                        | on/off      |
| Starting current               | 10 A, 10 ms |
| Power min                      | 1 W         |
| Power                          | 7.2 W       |
| Output current                 | 350 mA      |
| Degree of protection           | IP20        |
| Protection class               | II          |
| Flicker-free                   | Yes         |

**BB36 LED recessed spotlight set, switchable, with connection box**

Article no. 38497173

| Mounting technology         |   |
|-----------------------------|---|
| Mounting method             | Recessed mounting                         |
| Place of installation       | Ceiling-mounted                           |
| Adjustability               | Pivoted                                   |
| Swivel angle                | 20°                                       |
| Max. ceiling thickness      | 15 mm                                     |
| Further references          | No cover with thermal insulation material |
| Material cover              | Polycarbonat clear                        |
| Suitable for through-wiring | Yes                                       |

| Packing data            |  |
|-------------------------|--|
| Gross weight            | 0.274 kg   |
| Length of packaging     | 115 mm   |
| Packaging width         | 86 mm  |
| Packaging height        | 63 mm  |
| Disposal at end of life | <p>This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately.</p> <p>By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.</p> |

**Optional accessories**