

TECHNISCHE DATEN:

Aufbau

Hutmutter	Polyamid PA6 V-2
Dichtring	Polychloropren-Nitrilkautschuk CR/NBR
Zwischenstutzen	Polyamid PA6 V-2
Anschlussgewinde	metrisch, nach EN 60423

Eigenschaften

- integrierte Zugentlastung
- großer Dicht- und Klemmbereich
- Dichtbereich und Hutmutterabmessungen sind identisch mit der PERFECT Pg-Serie 50.0xx PAzzzz
- montagefreundlich
- UV- und Witterungsbeständigkeit gemäß UL 514B

Temperaturbereich	-20 °C / +100 °C (dynamisch) -40 °C (statisch, kurzzeitig)
-------------------	---

Schutzart IP68 - 5 bar

Prüfnorm UL 514B

UL / CSA-File E140310

Hinweis Angaben zu den Prüfergebnissen - siehe Anhang

TECHNICAL DATA:

Configuration

Dome nut	Polyamide PA6 V-2
Sealing ring	Polychloroprene-Nitrile rubber CR/NBR
Gland body	Polyamide PA6 V-2
Connecting thread	metric, as per EN 60423

Properties

- integrated anchorage
- wide sealing and clamping range
- sealing range and dome nut dimensions are identical to PERFECT Pg-series 50.0xx PAzzzz
- easy-to-install
- UV- and weather resistance according UL 514B


Temperature range	-20 °C / +100 °C (dynamic) -40 °C (static, short term)
-------------------	---

Protection grade IP68 - 5 bar

Test standard UL 514B

UL / CSA-File E140310

Comment details about test results - see annex



Merkmale

Anschlussgewinde Standardlänge

A	øC mm	L mm	SW1 mm	SW2 mm	H mm	
M12x1,5	3 - 6,5	8	15	15	31	100
M16x1,5	5 - 10	8	22	22	37	100
M20x1,5	6 - 12	8	24	24	38,5	100
M20x1,5	10 - 14	8	27	27	40,5	50
M25x1,5	13 - 18	8	33	33	45	50
M32x1,5	18 - 25	10	42	42	52,5	25
M40x1,5	22 - 32	10	53	53	61,5	10
M50x1,5	30 - 38	12	60	60	67,5	5
M63x1,5	34 - 44	12	65	65	67	5

Characteristics

Connecting thread standard length

RAL 7001 silbergrau silver grey	RAL 7035 lichtgrau light grey	RAL 9005 tiefschwarz jet black
Art.-Nr. / Part No.	Art.-Nr. / Part No.	Art.-Nr. / Part No.
50007M12PA	50007M12PA7035	50007M12PASW
50.011M16PA08	5011M16PA08/7035	50.011M16PA08/SW
50.013M20PA08	5013M20PA08/7035	50.013M20PA08/SW
50.016M20PA08	5016M20PA08/7035	50.016M20PA08/SW
50.021M25PA08	5021M25PA08/7035	50.021M25PA08/SW
50.029M32PA10	5029M32PA10/7035	50.029M32PA10/SW
50.036M40PA10	5036M40PA10/7035	50.036M40PA10/SW
50.042M50PA12	5042M50PA12/7035	50.042M50PA12/SW
50.048M63PA12	5048M63PA12/7035	50.048M63PA12/SW

Anschlussgewinde lang

A	øC mm	L mm	SW1 mm	SW2 mm	H mm	
M16x1,5	5 - 10	15	22	22	44	100
M20x1,5	6 - 12	11	24	24	41,5	100
M20x1,5	10 - 14	15	27	27	47,5	50
M25x1,5	13 - 18	15	33	33	52	50
M32x1,5	18 - 25	15	42	42	57	25
M40x1,5	22 - 32	18	53	53	69	10
M50x1,5	30 - 38	18	60	60	73,5	5
M63x1,5	34 - 44	18	65	65	73	5

Connecting thread long

RAL 7001 silbergrau silver grey	RAL 7035 lichtgrau light grey	RAL 9005 tiefschwarz jet black
Art.-Nr. / Part No.	Art.-Nr. / Part No.	Art.-Nr. / Part No.
50011M16PA	50011M16PA7035	50011M16PASW
50013M20PA	50013M20PA7035	50013M20PASW
50016M20PA	50016M20PA7035	50016M20PASW
50021M25PA	50021M25PA7035	50021M25PASW
50029M32PA	50029M32PA7035	50029M32PASW
50036M40PA	50036M40PA7035	50036M40PASW
50042M50PA	50042M50PA7035	50042M50PASW
50048M63PA	50048M63PA7035	50048M63PASW