MATERIAL SAFETY DATA SHEET

Date: Jan/16/2015 File No.: PH-W5-879D

1. Identification of the substance/preparation and of the company/undertaking

Identification of the product

Product name:

Chemical System:

Model:

Designated for RECHARGE?

Lithium Polymer Cell

LiCoO2/C (Li-polymer cell)

13450, 650mAh 3.7V, 2.405Wh

X Yes No

Manufacturer/supplier identification

Company:

Contact for information:

Emergency telephone No.:

Guangzhou Great Power Energy & Technology Co., Ltd.

922 Xicun Section, Shiliang Road, Shawan, Panyu,

Guangzhou, GD, PRC

0086-20-39196888

2. Composition/information on ingredients

Ingredient	Percent	CAS Index No./EC No.	Molar mass	Molecular formula	Symbol
Lithium cobaltate	31.6%	12190-79-3		LiCoO2	
Graphite	17.1%	7782-42-5		C	
Organic Electrolyte	13.2%	N/A			
Polypropylene	2.8%	N/A			
Copper	6.5%	7440-50-8		Cu	
Aluminum	28.8%	7429-90-5		Al	

Weight of metallic lithium per cell: 0g. There is no metallic lithium in the lithium polymer battery. The lithium polymer battery is with a Watt-hour rating \leq 20 Wh/Cell (cell), \leq 100 Wh (battery-pack).

3. Hazards identification

Health Hazards (Acute and Chronic):

For the battery cell, chemical materials are stored in a hermetically sealed aluminum laminate case, designed to withstand temperatures and pressures encountered during normal use. As a result, during normal use, there is no physical danger of ignition or explosion and chemical danger of hazardous materials leakage.

However, if exposed to a fire, added mechanical shocks, decomposed, or added electric stress by misuse the cell case will be breached and hazardous materials may be released. Moreover, if heated strongly by the surrounding fire, acrid gas may be emitted.

Carcinogenicity:

NTP: None IARC Monograph: None OSHA Regulated: None

Medical Conditions Generally Aggravated by Exposure:

An acute exposure will not generally aggravate any medical condition.

Human health effects:

Inhalation: The steam of the electrolyte has an anesthesia action and stimulates a respiratory tract.

Skin contact: The steam of the electrolyte stimulates a skin. The electrolyte skin contact causes a sore and the stimulation on the skin.

Eye contact: The steam of the electrolyte stimulates eyes. The electrolyte eye contact causes a sore and the stimulation on the eye. Inflammation of the eyes may occur.

Environmental effects:

Since a battery cell remains in the environment, do not throw out it into the environment.

Specific hazards:

If the electrolyte contacts with water, it may generate detrimental hydrogen fluoride.

Since the leaked electrolyte is inflammable liquid, do not bring close to fire.

4. First aid measures

After inhalation contact: Make the victim blow his/her nose, gargle. Seek medical attention if

necessary.

After skin contact: Remove contaminated clothes and shoes immediately. Immediately wash

extraneous matter or contact region with soap and plenty of water.

After eye contact: Do not rub eyes. Immediately flush eyes with water continuously for at least

15 minutes. Seek medical attention.

After ingestion contact: Make the victim vomit. Immediately seek medical attention.

5. Fire-fighting measures

fire-fighting:

Extinguishing Media: Plenty of water, CO₂ gas, nitrogen gas, chemical powder fire extinguishing

medium and fire foam.

When the battery burns with other combustibles simultaneously, take fire Specific methods of

extinguishing method which corresponds to the combustibles. Extinguish a fire

from the windward as much as possible.

Not available Flammable Limits:

6. Accidental release measures

The preferred response is to leave the area and allow the batteries to cool and the vapors to dissipate. Avoid skin and eye contact or inhalation of vapors. Remove spilled liquid with absorbent and incinerate.

7. Handling and storage

Avoid mechanical or electrical abuse. Batteries may explode or cause burns, if disassembled, crushed or exposed to fire or high temperatures. Do not short or install with incorrect polarity.

8. Exposure controls/personal protection

Specific control parameter:

Personal protective equipment:

Respiratory protection (Specify Type):

Ventilation:

Protective Gloves:

Eye protection:

Other Protective

(Clothing or Equipment):

Not necessary under conditions of normal use.

9. Physical and chemical properties

Appearance

Physical state:

Solid

Form:

Prismatic (Laminated)

Color:

Metallic color

Odor:

No odor

PH

N/A

Specific temperatures

Temperature ranges changes in physical state occur.

Flash point

N/A

Explosion properties

N/A N/A

Density Solubility

with indication of the solvent(s): Insoluble in water

10. Stability and reactivity

Stability:

Stable

Conditions to Avoid:

When cell is exposed to an external short-circuit, crushes, deformation, high

temperature above 100 degree C, it will cause heat generation and ignition. Avoid

direct sunlight and high humidity.

Hazardous Decomposition

Acrid or harmful gas is emitted during fire.

or By-products:

Materials to avoid:

Conductive materials, water, seawater, strong oxidizers and strong acids.

Hazardous polymerization will not occur.

11. Toxicological information

Acute toxicity:

Copper

60-100mg sized coarse particulate causes a gastrointestinal disturbance with nausea and inflammation. TDLo, hypodermic - Rabbit 375mg/kg

Organic electrolyte

LD50, oral - Rat 2,000mg/kg or more

Further toxicological information:

Aluminum

By the long-term inhalation of coarse particulate or fume, it is possible to

cause lung damage (aluminum lungs).

Lithium Cobaltate

By the long-term inhalation of coarse particulate or vapor of cobalt, it is possible to cause the serious respiratory-organs disease. Skin reaction or a

lung disease for allergic or hypersensitive person may be caused.

Graphite

Long-term inhalation of high levels of graphite coarse particulate may

cause lung disease or a tracheal disease.

12. Ecological information

Ecotoxic effects: N/A
Further ecological data: N/A

13. Disposal considerations

Great Power encourages battery recycling. Our Li-polymer cells are recyclable through the Rechargeable Battery Recycling Corporation's (RBRC) *Charge Up to Recycle! Program*. For information call 1-800-8-BATTERY or see their website at www.rbrc.org. Li-Polymer batteries must be handled in accordance with all applicable state and federal laws and regulations.

DO NOT INCINERATE or subject battery cells to temperatures in excess of 212° F. Such treatment can vaporize the liquid electrolyte causing cell rupture. Do not use in combination with fresh and used lithium batteries neither with other type of battery.

14. Transport information

International transport regulations:

1. International Air Transport Association (IATA) pursuant to Packing

Instruction 965-967, Section II

2. International Maritime Dangerous Goods Code (IMDG) pursuant to

Special Provisions A188 and A230.

4. U.S. hazardous materials regulations pursuant to 49 CFR 173.185 and

Special Provision A188.

UN-No.:

3480 and 3481

IATA Packaging Instruction

Packing Instruction 965-967 Section II

Great Power Li-polymer cells pass the tests defined in UN model regulation section 38.3. Cells and batteries are packed according to the requirement of 56th Edition of the IATA Dangerous Goods Regulations (DGR).

If Great Power Li-polymer cells are used to construct battery packs, the assembler of that pack is responsible to ensure the battery has been tested in accordance with the requirements contained in the UN Model Regulations, Manual of Test and Criteria. Part III, subsection 38.3.

15. Regulatory information

N/A

16. Other information

Make people:

Professional post: R&D Engineer

Make unit:

Name: R&D Department

eer Name(sign): Jacky Lee Phone: 0086-20-39196888

Address: R&D Dept., Panyu Plant., Date of issue: 2015/01/16

DISCLAIMER:

The information and recommendations set forth are made in good faith and believed to be accurate as of the date of preparation. Guangzhou Great Power Energy & Technology Co.,Ltd makes no warranty, expressed or implied, with respect to this information and disclaims all liabilities from reliance on it.

