

UN 38.3 Test Summary Report

Lithium Cell or Battery Test Summary in Accordance with Section 2.9.4 UN Model Regulations and Sub-section 38.3 of the UN Manual of Tests and Criteria, Part III, subsection 38.3.5

| | |
|---|--------------------------------------|
| <p>[a] <input checked="" type="checkbox"/> Cell <input type="checkbox"/> Battery <input type="checkbox"/> Product <input checked="" type="checkbox"/> Tested Type Part #: SL-2770 <input type="checkbox"/> Same Type Part #:</p> | <p>[d] Unique report ID: 15Q-607</p> |
| <p>[b] Manufacturer Tadiran Batteries Ltd. P.O. Box 1 Kiryat Ekron Israel 70500 T. +972 8 9 44 560 sales@tadiran-batt.com www.tadiran.com</p> | <p>[e] Report date: 2003.06.01</p> |
| <p>[c] Test Laboratory Tadiran Batteries Ltd. P.O. Box 1 Kiryat Ekron Israel 70500 T. +972 8 9 44 560 sales@tadiran-batt.com www.tadiran.com</p> | |

Same Type Part Numbers # (all): Standard: 11 2 17701 00, Tags: 11 2 17702 00, Pins: 11 2 17703 00, Pins radial: 11 2 17706 00, Polarised tags: 11 2 17708 00, all other configurations with harness and cable of this cell with part number: 11 2 1770x xx

[f] (i) Li-ion Li-metal.

(iv) **Description:** Primary (non-rechargeable) 3.7 V Lithium Thionyl Chloride (Li-SOCI₂) battery, assembled from 1 (one) "C" sized SL-2770 cell. The SL-2770 cell may come with optional suffixes consisting of a "/" followed by one or more letters and a digit. These suffixes indicate different types of finishing to the cell (for example, S-Standard, T-Tab, P-Pin, etc.).
Tadiran manufactures all cells/batteries under a quality management system as required under this regulation.

(ii) Mass: 50 g
(iii) Watt hour rating or Lithium content: 2.5 g
(v) Cell Battery Product. Model number/Part number: SL-2770

| [g] List of Tests Conducted | Result (Pass / Fail / N.A.) | Test record reference |
|--|-----------------------------|-----------------------|
| 38.3.4.1 T.1: Altitude simulation | Pass | Page 5 |
| 38.3.4.2 T.2: Thermal test | Pass | Page 6 |
| 38.3.4.3 T.3: Vibration | Pass | Page 7 |
| 38.3.4.4 T.4: Shock | Pass | Page 8 |
| 38.3.4.5 T.5: External short circuit | Pass | Page 9 |
| 38.3.4.6 T.6: Impact/Crush (cell only test) | Pass | Page 10 |
| 38.3.4.7 T.7: Overcharge (N.A for Li-metal only) | N.A. | N.A. |
| 38.3.4.8 T.8: Forced discharge (cell only test) | Pass | Page 11 |

[h] Battery assembly: Not Applicable. UN38.3.3 (f) UN38.3.3 (g)

[i] Test Reference: UN Manual of Tests and Criteria, Part III, sub-section 38.3. *third revised edition, am.1*

| | | |
|--|---|---|
| <p>[j] Signatory A. Date: 2018.02.12 Name: Marc Henn Title: Application Engineering Manager Signature: </p> |  | <p>[j] Signatory B. Date: 2018.02.12 Name: Olaf G. Lichtlein Title: General Manager Signature: </p> |
|--|---|---|

Important! The above signatory / signatories affirm that this document is a true and correct summary of the original individual tests and test data. The original test data is confidential information available to competent State Authorities with valid identification and only upon their formal request. Disclosure of the original test data to any other entity upon its request will be considered by Tadiran and, should Tadiran consider this request is with merit, may be subject to the prior execution of a nondisclosure agreement.