




**BYAM-S MAXI LED Surface-mounted ceiling light, 3CCT, Multipower**  
**17/24 W, IP65, switchable**  
 Article no. 12515073



#### Tender

LED surface-mounted ceiling downlight, 3CCT, Multipower 17/24 W, IP65, switchable, luminaire length 330 mm, luminaire width 330 mm, height 50 mm, weight 1.075 kg, with rotationally symmetrical narrow-wide beam light distribution. Opal plastic cover, rated luminous flux 2,622 lm, rated wattage 1 x 24 W, light color warm white to daylight white, most similar color temperature (CCT) 3,000 - 5,700 K, general color rendering index CRI > 80, service life L70/B50 at 25 °C: 50,000 h, housing material: plastic, color: white, permissible ambient temperature (ta): -20 °C - +25 °C, protection class (EN 61140): II, degree of protection (DIN EN 60529): IP65, degree of impact resistance according to IEC62262: IK10. With electronic control gear, switchable.

#### Product Benefits

- Flat surface-mounted light (length 330 mm, width 330 mm, height 50 mm, with multipower function 17 W / 24 W) for ceiling or wall mounting.
- 3 CCT adjustable: 3,000 K / 4,000 K / 5,700 K.
- Luminous flux 24 W: 3,000 K: 2,622 lm, 4,000 K: 2,850 lm, 5,700 K: 2,736 lm
- Available in three sizes and 2 shapes (round / square).
- Switchable version.

**BYAM-S MAXI LED Surface-mounted ceiling light, 3CCT, Multipower  
 17/24 W, IP65, switchable**  
 Article no. 12515073

Article data	
Article no.	12515073
GTIN	4255752500841
Series name	BYAM-S MAXI
Short description	LED Surface-mounted ceiling light, 3CCT, Multipower 17/24 W, IP65, switchable
Material	Plastic
Colour	White
Type of surface	Matt
Shape	Square
Length	330 mm
Width	330 mm
Hight	50 mm
Scope of delivery	incl. converter with power and color temperature selection option for connection to 230 V mains voltage, switchable
Weight	1.075 kg
Conformance	CE, UKCA

Lighting technology	
Colour temperature	3.000 K / 4.000 K / 5.700 K
Light colour	White
Color Temperature 1	3,000 K
Color Temperature 2	4,000 K
Color Temperature 3	5,700 K
Light output	Direct
Luminous flux	2,622 lm
Luminous flux 1	2,700 lm
Luminous flux 2	2,790 lm
Luminous flux 3	2,700 lm
System efficiency	109 lm/W
Colour rendering	CRI > 80
Beam angle	120°
Light sharing	Symmetric
Adjustable color temperature	Stages

Operating technology of the luminaire	
System output	24 W
Voltage type	AC
AC nominal voltage max	230 V
Frequency max	50 Hz
Lamp	LED
Protection class	II
Degree of protection	IP65
Dimmable	No
Control	on/off
Bulb change possible	No
Rated life time L70/B50 at 25 °C	50,000 h
Energy efficiency class	F

Mounting technology	
Mounting method	Surface mounting
Place of installation	Ceiling-mounted
Adjustability	Not adjustable
Impact resistance	IK10
Material cover	Plastic, opal

**BYAM-S MAXI LED Surface-mounted ceiling light, 3CCT, Multipower  
17/24 W, IP65, switchable**  
Article no. 12515073

Packing data	
Gross weight	1.125 kg
Length of packaging	340 mm
Packaging width	340 mm
Packaging height	60 mm
Disposal at end of life	<p>This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately.</p> <p>By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.</p>

Optional accessories	
Article no.: 81502000	
Mounting spring set for use as recessed ceiling light	
<a href="https://www.brumberg.com/fileadmin/products/Datenblatt_81502000_2021_DE.pdf">https://www.brumberg.com/fileadmin/products/Datenblatt_81502000_2021_DE.pdf</a>	