



ABACO LED recessed spotlight set, trailing edge dimmable, IP44

Article no. 39415153


Tender

LED recessed spotlight set, trailing edge dimmable, IP44, Square. Toolless ceiling installation by installation springs. Ceiling cut-out Ø 68 mm, Installation depth 38 mm, Length 83 mm, Width 83 mm, Weight 0,200 kg, Reflector silver with rotationssymmetrical, deep, wide distributed light intensity. Cover plastic, transparent. Luminous flux 1.010 lm, Power 1 x 8 W, Light colour warm white, Correlated color temperature (CCT) 3.000 K, Colour rendering index CRI > 80, Rated life time L80/B50 at 25 °C: 50.000 h, Housing material: Aluminium / PMMA, Colour: Nickel, Permissible ambient temperature (ta): -20 °C - +25 °C, Protection class (EN 61140): II, Degree of protection (DIN EN 60529): IP44. With electronic driver, Trailing-edge phase dimmable.

Product Benefits

- Protection class IP44 for indoor damp locations
- Standard ceiling cut-out 68 mm - low installation depth 40 mm
- Dimmable as standard via trailing edge phase control (supplied as a set)

ABACO LED recessed spotlight set, trailing edge dimmable, IP44

Article no. 39415153

Article data	
Article no.	39415153
GTIN	4255752504429
Series name	ABACO
Short description	LED recessed spotlight set, trailing edge dimmable, IP44
Material	Aluminium / PMMA
Colour	Nickel
Type of surface	Matt
Shape	Square
Built-in diameter	68 mm
Installation depth	38 mm
Length	83 mm
Width	83 mm
Hight	3 mm
Scope of delivery	incl. connection box, 3-pole for through-wiring
Weight	0.200 kg
Conformance	CE, UKCA

Lighting technology	
Colour temperature	3.000 K
Light colour	White
Light output	Direct
Luminous flux	1,010 lm
System efficiency	126 lm/W
Colour rendering	CRI > 80
Reflector	Faceted
Reflector colour	silver
Beam angle	36°
Light sharing	Symmetric
Adjustable color temperature	No

Operating technology of the luminaire	
System output	8 W
Voltage type	AC
AC nominal voltage max	230 V
Frequency max	50 Hz
Lamp	LED
Protection class	II
Degree of protection	IP44
Protection class on the ceiling side	IP20
Dimmable	Yes
Control	Trailing-edge phase
Bulb change possible	The light source of this luminaire may only be replaced by the manufacturer or a service technician commissioned by him or a similarly qualified person.
Rated life time L80/B50 at 25 °C	50.000 h

Mounting technology	
Mounting method	Recessed mounting
Place of installation	Ceiling-mounted
Adjustability	Pivoted
Swivel angle	15°
Max. ceiling thickness	25 mm
Further references	No cover with thermal insulation material
Material cover	Plastic, transparent
Circlip	Without circlip
Suitable for through-wiring	Yes

ABACO LED recessed spotlight set, trailing edge dimmable, IP44
Article no. 39415153

Packing data	
Gross weight	0.23 kg
Length of packaging	105 mm
Packaging width	105 mm
Packaging hight	90 mm
Disposal at end of life	<p>This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately.</p> <p>By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.</p>

Optional accessories